

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Standard extruded heatsinks](#) » [SK 501 ...](#) » [SK 501](#)



▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
 - [Standard extruded heatsinks](#)
 - Extruded heatsinks for lock-in retaining spring
 - Extruded heatsinks for PCB mounting
 - Extruded heatsinks for DC/DC converter
 - Retaining springs for transistors
 - U-Extruded heatsinks
 - Die-cast heatsinks
 - Fin coolers
 - Fluid coolers
 - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
- Heatsinks and active heatsinks for processors
- Board Level heatsinks
- Cooling aggregates
- Accessories for electronic components

► Cases f.case

► Connectors f.con

Standard extruded heatsinks

SK 501 ...

SK 501 1000 AL

300 x 40mm, weigth reduced like SK 56

[add to request](#) 



Features

Technical Drawing

Service

width	300 mm
height	40 mm
plate thickness	10 mm
length	1000 mm
thermal resistance R_{th}	0.5 - 0.3 K/W
surface	raw degreased aluminium