Product data sheet

Miniature connectors



Product description M16 Male cable connector, Contacts: 24, 6.0-8.0 mm, unshielded, solder, IP67


Area series 723
Part no. 09 0495 70 24


Illustration

Scale drawing

Contact arrangement (Plug-in side)







You can find the assembly instructions on the next page.

Technical data

General features

Part no.	09 0495 70 24
Connector design	Male cable connector
Version	Connector pin straight
Connector locking system	screw
Termination	solder
Degree of protection	IP67
Cross-sectional area	0.14 mm ² / AWG 26
Cable outlet	6.0-8.0 mm
Temperature range from/to	-40 °C / 95 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	37.48
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	60 V
Rated impulse voltage	500 V
Rated current	1.0 A
Insulation resistance	≥ 10 ¹⁰ Ω
Pollution degree	1
Overvoltage category	1
Insulating material group	III
EMC compliance	unshielded

Material

Housing material	PA
Contact body material	PBT (UL94 V-0)

Product data sheet

Miniature connectors



Product description M16 Male cable connector, Contacts: 24, 6.0-8.0 mm, unshielded, solder, IP67

Area series 723
Part no. 09 0495 70 24

 Contact material
 CuZn (brass)

 Contact plating
 Au (gold)

 REACH SVHC
 CAS 96-45-7 (Imidazolidine-2-thione)

 SCIP number
 CAS 7439-92-1 (Lead)


 SCIP number
 f9558135-769e-433f-b16c-5d71698b5bbb

Classifications

eCl@ss 11.1	27-44-01-09	
FTIM 9 0	FC003569	

Declarations of conformity

Assembly instructions



Product data sheet

Miniature connectors



Product description M16 Male cable connector, Contacts: 24, 6.0-8.0 mm, unshielded, solder, IP67

Area series 723
Part no. 09 0495 70 24

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

The plug connector is not suitable for mains voltages Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

The protection class specification applies on condition that the four mounting holes are made as blind holes.