





由Autodesk 教育版产品制作

由Autodesk 教育版产品制作



PCB HOLES(THE PATTERN SIDE)

NOTE:GENERAL TOLERANCE:±0.1mm



NOTES:

1. HOUSING: SEE NOTES,
TERMINAL: SEE NOTES.
SHELL: SEE NOTES.

SPECIFICATION:

1. ELECTRICAL CHARACTERISTIC:
CONTACT RESISTANCE: 30MΩ MAX
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1MIN
INSULATION RESISTANCE: 1000MΩ MIN
2. MECHANICAL CHARACTERISTIC:
INSERTION FORCE: 35N(3.57KGF) MAX
EXTRACTION FORCE: 10~35N(1.02~3.57KGF)MIN
DURABILITY: 1500 CYCLES EXTRACTION FORCE:10~35N
5000 CYCLES MIN
5000 CYCLES EXTRACTION FORCE:3~35N
3. ENVIRONMENTAL:
OPERATING TEMPERATURE: -55℃+85℃
4. Contact finish:
01:Selective Gold Flash
02:Selective Gold 3U"
03:Selective Gold 5U"
04:Selective Gold 15U"
05:Selective Gold 30U"

品
PRODUCT CHART DWG

公差等级 TOLERANCE UNLESS OTHERWISE			
X	±0.20	X	±5.°
.X	±0.15	.X	±2.°
.XX	±0.10	.XX	±1.°
.XXX	±0.05	.XXX	±0.5°

深圳市精拓金电子有限公司

单位 UNITS	MM	图号 DRAWING	Z-Y-B	产品号 PRODUCT PART NO	909-351A1023D10100		
比例 SCALE	1:1	检查 CHKD		品名 PRODUCT NO	AF10.0B款四脚有边铁壳PBT黑胶 DIP无耳朵		
日期 DATE	2010.05.06	?? APPD		图名 VIEW		版本 VER	AO