



ENVIRONMENTAL:PROTECTION: IP67 IN MATED AND
LOCKED POSITION



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																	
FUNCTIONAL SYMBOLS		DIMENSION UNITS		SCALE		CURRENT REV DESC: CHANGED DIMENSIONING STYLE OF OVERALL LENGTH TO END TO END, UPDATED NOTES AND SORTED PART LIST USING CABLE TYPES ON SHEET 3				molex							
		mm		2:1													
		GENERAL TOLERANCES (UNLESS SPECIFIED)				CSE M12 XP AC FE RA XM SE UNSH											
		ANGULAR TOL ± 1.0 °															
		4 PLACES		±								EC NO: 789428 DRWN: AKABADI 2023/02/27 CHKD: RSILLER 2024/07/02 APPR: RSILLER 2024/07/02					
3 PLACES		±															
2 PLACES		± 0.05															
DIVISIONAL SYMBOLS		1 PLACE		± 0.3		INITIAL REVISION: DRWN: SSM 2021/12/13 APPR: RSILLER 2022/02/28				DOCUMENT NUMBER		DOC TYPE		DOC PART		REVISION	
		0 PLACES		± 0.5						1200656607		PSD		000		B	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
						A3-SIZE		120065		SEE SHEET 3		GENERAL MARKET		1 OF 3			

CODING REQUIRED TO IEC 61076-2-101

FORMAT: master-lib-prod-A3

PART LIST

MOLEX PN	ENGINEERING No	L [mm]
3P CABLE B30		
1200652259	803001B30M010	1000
1200652260	803001B30M020	2000
1200652261	803001B30M050	5000
1200652262	803001B30M100	10000
4P CABLE B30		
1200652263	804001B30M010	1000
1200652264	804001B30M020	2000
1200659470	804001B30M030	3000
1200652265	804001B30M050	5000
1200659807	804001B30M083	8300
1200652266	804001B30M100	10000
1200659401	804001B30M150	15000
1200659471	804001B30M200	20000
1200659472	804001B30M250	25000
1200659473	804001B30M300	30000
5P CABLE B30		
1200659522	805001B30M010	1000
1200659523	805001B30M020	2000
1200656665	805001B30M030	3000
1200659524	805001B30M050	5000
1200659525	805001B30M100	10000
1200659748	805001B30M150	15000
1200656484	805001B30M200	20000
8P CABLE B41		
1200652310	808001B41M010	1000
1200652311	808001B41M020	2000
1200652312	808001B41M050	5000
1200659789	808001B41M083	8300
1200652313	808001B41M100	10000
1200656022	808001B41M150	15000
1200656486	808001B41M200	20000
5P CABLE B42		
1200652267	805001B42M010	1000
1200652268	805001B42M020	2000
1200652269	805001B42M050	5000
1200652270	805001B42M100	10000
1200659542	805001B42M200	20000

MOLEX PN	ENG No.	L [mm]
4P CABLE B33		
1200657144	804001B33M005A	500
1200656607	804001B33M010A	1000
1200656608	804001B33M020A	2000
1200656609	804001B33M030A	3000
1200656610	804001B33M050A	5000
1200656611	804001B33M100A	10000
1200656612	804001B33M150A	15000
1200656613	804001B33M200A	20000
5P CABLE B33		
1200657181	805001B33M005A	500
1200656658	805001B33M010A	1000
1200656659	805001B33M020A	2000
1200656660	805001B33M030A	3000
1200656661	805001B33M050A	5000
1200656662	805001B33M100A	10000
1200656663	805001B33M150A	15000
1200656664	805001B33M200A	20000
1200657182	805001B33M300A	30000
1200657183	805001B33M400A	40000
1200657184	805001B33M500A	50000
4P CABLE B55		
1200656627	804001B55M010Y	1000
1200656628	804001B55M020Y	2000
1200656629	804001B55M030Y	3000
1200656630	804001B55M050Y	5000
1200656631	804001B55M100Y	10000
1200656632	804001B55M150Y	15000
1200656633	804001B55M200Y	20000
5P CABLE B55		
1200656666	805001B55M010Y	1000
1200656667	805001B55M020Y	2000
1200656668	805001B55M030Y	3000
1200656669	805001B55M050Y	5000
1200656670	805001B55M100Y	10000
1200656671	805001B55M150Y	15000
1200656672	805001B55M200Y	20000

MOLEX PN	ENG No.	L [mm]
4P CABLE B36		
1200656852	804001B36M0107Y	1000
1200656391	804001B36M0207H	2000
1200659432	804001B36M0207Y	2000
1200656392	804001B36M0507H	5000
1200659433	804001B36M0507Y	5000
1200656393	804001B36M1007H	10000
1200659434	804001B36M1007Y	10000

CABLE LENGTH TOLERANCES

LENGTH	TOLERANCE
0 m - 1 m	+40 mm
>1 m - 5 m	+60 mm
>5 m - 10 m	+80 mm
>10 m - 20 m	+140 mm
>20 m - 30 m	+160 mm
>30 m	+1% length

NOTE:
* (STAR) - INDICATES THESE PNS ONLY HAVE ID CARRIER IN BOM.


DOCUMENT STATUS	P1	RELEASE DATE	2024/07/02	09:17:37
-----------------	----	--------------	------------	----------

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
	DIMENSION UNITS		SCALE		CURRENT REV DESC: CHANGED DIMENSIONINGSTYLE OF OVERALL LENGTH TO END TO END. UPDATED NOTES AND SORTED PART LIST USING CABLE TYPES ON SHEET 3			molex							
	mm		1:1												
	GENERAL TOLERANCES (UNLESS SPECIFIED)														
	ANGULAR TOL ± 1.0 °														
	4 PLACES ±							EC NO: 789428			CSE M12 XP AC FE RA XM SE UNSH				
	3 PLACES ±				DRWN: AKABADI 2023/02/27										
	2 PLACES ± 0.05				CHK'D: RSILLER 2024/07/02										
	1 PLACE ± 0.3				APPR: RSILLER 2024/07/02			PRODUCT CUSTOMER DRAWING							
	0 PLACES ± 0.5				INITIAL REVISION:										
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				DRWN: SSM 2021/12/13			DOCUMENT NUMBER			DOC TYPE	DOC PART	REVISION			
				APPR: RSILLER 2022/02/28			1200656607			PSD	000	B			
				THIRD ANGLE PROJECTION			MATERIAL NUMBER			CUSTOMER			SHEET NUMBER		
							DRAWING			A3-SIZE			120065		
							SEE SHEET 3			GENERAL MARKET			3 OF 3		


FEMALE PLUG M12 90° ANGLED

NOTES:


RATED VOLTAGE: 3, 4 contacts 250V
5 contacts 60V
8 contacts 30V
RATED CURRENT: 3, 4, 5 contacts 4A
8 contacts 2A
PROTECTION CLASS: IP 67
TEMPERATURE: -25°C / +80°C



Thicker Overmold for Cables — with bigger Outer Diameter ($\phi > 6$)




CONTACTS POSITION FRONT VIEW:

3 CONTACTS		4 CONTACTS		5 CONTACTS		8 CONTACTS	
							
PIN	WIRE	PIN	WIRE	PIN	WIRE	PIN	WIRE
1	BROWN	1	BROWN	1	BROWN	1	WHITE
2	---	2	WHITE	2	WHITE	2	BROWN
3	BLUE	3	BLUE	3	BLUE	3	GREEN
4	BLACK	4	BLACK	4	BLACK	4	YELLOW
5	---	5	---	5	GREY OR GREEN/YELLOW	5	GREY
						6	PINK
						7	BLUE
						8	RED
CODING REQUIRED TO IEC 61076-2-101							

FOR OPTIONS SEE - NUMERICAL CODE - ON SHEET 2				
8	-	I/D CARRIER	PVC	TRANSPARENT
7	1	LABEL	VINYL	YELLOW
6	-	CABLE	SEE SHEET 2	---
5	-	OVERMOLDING	TPU	SEE SHEET 2
4	1	COUPLING NUT FEMALE	BRASS	SEE SHEET 2
3	1	INSERT FEMALE	PUR	BLACK
2	1	ORING	FPM	RED
1	3 / 4 / 5	CONTACT M12 FEMALE	BRONZE	SELECTIVE Au OVER Ni
	8		BRASS	SELECTIVE Au OVER Ni
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH / COLOR

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
	DIMENSION UNITS		SCALE		molex CSE M12 XP AC FE RA XM SE UNSH										
F A = 0	mm		2:1												
F E = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)				CURRENT REV DESC: P/N'S ADDED EC NO: 667684 DRWN: RSCHIEBER2021/06/21 CHK'D: RSILLER2021/06/22 APPR: RSILLER2021/06/22 INITIAL REVISION: DRWN: FSCHAFHAUSER2014/02/10 APPR: CBURGER2014/05/07										
F F = 0	ANGULAR TOL ± 1.0°														
DIVISIONAL SYMBOLS	4 PLACES		±												
	3 PLACES		±												
	2 PLACES		± 0.05												
	1 PLACE		± 0.3												
	0 PLACES		± 0.5												
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
						A3-SIZE		120065		SEE SHEET 3		GENERAL MARKET		1 OF 3	
										SD-120065-076		PSD		001 A5	

ENGINEERING NO. - NUMERICAL CODE (Available parts see PART LIST table. Others on request).



CABLE INFORMATION (for more information see Cable Data Sheet).

CABLE TYPE	NO. OF WIRES	CROSS SECTION	CABLE JACKET	UL	CSA	STATIC: TEMP. / BENDING RADIUS	DYNAMIC: TEMP. / BENDING RADIUS	DRAW CHAIN TESTED	OTHER	CABLE SPEC. DRAWING
B30	3 / 4 / 5	0.34mm²	TPU BLACK	STYLE 21215	YES	-40°C to +90°C, 5xO.D.	-25°C to +80°C, 7.5xO.D.	5 MIO CYCLES	WELD SLAG RESISTANCE	SD-120209-001
B42	5									SD-120209-001
B41	8	0.25mm²	SD-120209-006							
B36	4	0.34mm²	TPU ORANGE							SD-120209-001
B33	4 / 5	0.34mm²	TPU GRAY							SD-120209-001
B55	4 / 5	0.34mm²	TPU YELLOW							1552200001 PS

DOCUMENT STATUS	P1	RELEASE DATE	2021/06/22	13:20:30
-----------------	----	--------------	------------	----------

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
DIVISIONAL SYMBOLS	DIMENSION UNITS		SCALE		CURRENT REV DESC: P/N'S ADDED				molex						
	mm		1:1												
	GENERAL TOLERANCES (UNLESS SPECIFIED)								CSE M12 XP AC FE RA XM SE UNSH						
	ANGULAR TOL ± 1.0 °														
	4 PLACES		±		EC NO: 667684										
	3 PLACES		±		DRWN: RSCHIEBER 2021/06/21										
	2 PLACES		± 0.05		CHK'D: RSILLER 2021/06/22										
1 PLACE		± 0.3		APPR: RSILLER 2021/06/22											
0 PLACES		± 0.5		INITIAL REVISION:				PRODUCT CUSTOMER DRAWING							
DRWN: FSCHAFHAUSER 2014/02/10				DOCUMENT NUMBER				DOC TYPE		DOC PART		REVISION			
APPR: CBURGER 2014/05/07				SD-120065-076				PSD		001		A5			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
						A3-SIZE		120065		SEE SHEET 3		GENERAL MARKET		2 OF 3	

PART LIST


Lp.	MOLEX PN	ENGINEERING No	L+Tol. [mm]
1	1200652259	803001B30M010	1000 +40
2	1200652260	803001B30M020	2000 +60
3	1200652261	803001B30M050	5000 +60
4	1200652262	803001B30M100	10000 +80
5	1200652263	804001B30M010	1000 +40
6	1200652264	804001B30M020	2000 +60
7	1200652265	804001B30M050	5000 +60
8	1200652266	804001B30M100	10000 +80
9	1200659401	804001B30M150	15000 +160
10	1200659470	804001B30M030	3000 +60
11	1200659471	804001B30M200	20000 +160
12	1200659472	804001B30M250	25000 +160
13	1200659473	804001B30M300	30000 +300
14	1200659522	805001B30M010	1000 +40
15	1200659523	805001B30M020	2000 +60
16	1200659524	805001B30M050	5000 +60
17	1200659525	805001B30M100	10000 +80
18	1200659748	805001B30M150	15000 +160
19	1200659807	804001B30M083	8300 +80
20	1200652310	808001B41M010	1000 +40
21	1200652311	808001B41M020	2000 +60
22	1200652312	808001B41M050	5000 +60
23	1200652313	808001B41M100	10000 +80
24	1200656022	808001B41M150	15000 +160
25	1200659789	808001B41M083	8300 +80
26	1200652267	805001B42M010	1000 +40
27	1200652268	805001B42M020	2000 +60
28	1200652269	805001B42M050	5000 +60
29	1200652270	805001B42M100	10000 +80
30	1200659542	805001B42M200	20000 +160
31	1200656391	804001B36M0207H	2000 +60
32	1200656392	804001B36M0507H	5000 +60
33	1200656393	804001B36M1007H	10000 +80
34	1200656484	805001B30M200	20000 +160
35	1200656486	808001B41M200	20000 +160
36	*1200659432	804001B36M0207Y	2000 +60
37	*1200659433	804001B36M0507Y	5000 +60
38	*1200659434	804001B36M1007Y	10000 +80
39	1200656607	804001B33M010A	1000 +40
40	1200656608	804001B33M020A	2000 +60

NOTE:

* (STAR) - INDICATES THESE PNS ONLY HAVE ID CARRIER IN BOM.

DOCUMENT STATUS	P1	RELEASE DATE	2021/06/22	13:20:30
-----------------	----	--------------	------------	----------

[illegible]

FUNCTIONAL SYMBOLS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION													
DIVISIONAL SYMBOLS		DIMENSION UNITS		SCALE		CURRENT REV DESC: P/N'S ADDED				molex					
F _A = 0		mm		1:1											
F _E = 0		GENERAL TOLERANCES (UNLESS SPECIFIED)													
F _E = 0		ANGULAR TOL ± 1.0 °													
		4 PLACES		±											
		3 PLACES		±		EC NO: 667684				CSE M12 XP AC FE RA XM SE UNSH					
		2 PLACES		± 0.05		DRWN: RSCHIEBER 2021/06/21									
		1 PLACE		± 0.3		CHK'D: RSILLER 2021/06/22									
		0 PLACES		± 0.5		APPR: RSILLER 2021/06/22				PRODUCT CUSTOMER DRAWING					
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION	
										SD-120065-076		PSD	001	A5	
						A3-SIZE		120065		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
										SEE SHEET 3		GENERAL MARKET		3 OF 3	