

1511556

<https://www.phoenixcontact.com/us/products/1511556>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Socket M23, 19-pos., angled, shielded, with shielded, connected master cable, length: 25 m

Commercial data

Item number	1511556
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	AB34
Product key	ABRDCB
GTIN	4017918904326
Weight per piece (including packing)	5,952 g
Weight per piece (excluding packing)	5,860.001 g
Customs tariff number	85444290
Country of origin	DE

RCK-TWGM/BL16+3/25,0PUR SH - Master cable



1511556
<https://www.phoenixcontact.com/us/products/1511556>

Technical data

Product properties

Product type	Master cable, assembled
Number of positions	19
Data management status	
Article revision	05

Electrical properties

Nominal voltage U_N	48 V AC
	60 V DC

Signaling

Status display present	No
------------------------	----

Material specifications

Material Housing	PUR
Material of contact, master cable side	CU alloy
Material of the contact carrier on the master cable side	PA
Material of contact surface, master cable side	gold-plated

Connector

Connection 1

Head design	Socket
Head cable outlet	angled
Head thread type	M23

Connection 2

Head design	free cable end
-------------	----------------

Cable/line

Cable length	25 m
--------------	------

PUR/PVC shielded, black [PUR]

Dimensional drawing	
Number of positions	19
Shielded	yes

RCK-TWGM/BL16+3/25,0PUR SH - Master cable



1511556

<https://www.phoenixcontact.com/us/products/1511556>

Cable type	PUR/PVC shielded, black [PUR]
Conductor structure signal line	64x 0.10 mm
AWG signal line	20
Conductor cross section	16x 0.5 mm ² (Signal line) 3x 1 mm ² (Power supply)
External cable diameter	11.60 mm ±0.3 mm
Outer sheath, material	PUR
External sheath, color	deep black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, green/yellow, white, green, yellow, gray, pink, red, black, violet, gray/pink, red/blue, white/green, brown/green, white/yellow, yellow/brown, white/gray, gray/brown
Overall twist	Wires twisted in layers
Nominal voltage, cable	300 V
Test voltage	2000 V
Dynamic load capacity (bending)	Max. bending cycles: 1500000, Bending radius: 10 x D, Traversing path: 2 m, Traversing rate: 2 m/s
Flame resistance	DIN EN 50265
Resistance to oil	according to VDE 0472 Part 803
Other resistance	Highly resistant to acids, alkaline solutions and solvents
Special properties	Silicone-free Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	-40 °C ... 90 °C (cable, fixed installation) -5 °C ... 80 °C (Cable, flexible installation)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 IP67
Ambient temperature (operation)	-40 °C ... 125 °C

Mounting


Thread type	()
-------------	----

1511556

<https://www.phoenixcontact.com/us/products/1511556>


Drawings

Schematic diagram



Pin assignment M23 socket, 19-pos., female side view

Circuit diagram



RCK-TWGM/BL16+3/25,0PUR SH - Master cable



1511556

<https://www.phoenixcontact.com/us/products/1511556>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1511556>



EAC

Approval ID: 19060508

RCK-TWGM/BL16+3/25,0PUR SH - Master cable



1511556

<https://www.phoenixcontact.com/us/products/1511556>

Classifications

ECLASS

ECLASS-11.0	27060311
ECLASS-12.0	27060311
ECLASS-13.0	27060311

ETIM

ETIM 9.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	52f1c2d9-db29-4493-8658-5d1c8d194245