




- excellent power handling
- small size
- 7 sections
- temperature stable
- LTCC construction , and has good moisture resistance, corrosion resistance, high reliability.

- harmonic rejection
- VHF/UHF transmitters/receivers
- Base Station of Mobile Communication, lab use.

Parameter		Frequency(MHz)	Min.	Typ.	Max.	Unit
Pass Band	Insertion Loss	DC-180	-	-	1.0	dB
	Freq.Cut-Off	270	-	3.0	-	dB
	VSWR	DC-180	-	1.2	-	:1
Stop Band	Rejection Loss	370-525	20	-	-	dB
		525-2350	-	40	-	dB
	VSWR	2350-6400	-	20	-	dB
		370-6400	-	17	-	:1

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)
40	0.25	1.06
100	0.43	1.06
180	0.80	1.14
270	3.38	2.42
300	7.97	5.13
325	14.52	8.36
370	34.38	10.62
525	43.48	10.42
950	44.53	42.37
1700	47.20	61.79
2350	61.70	65.80
4500	29.67	71.94
6400	24.99	56.91
7500	22.12	18.86
9000	21.74	3.99



NOTES: 1. COPLANAR WAVEGUIDE PARAMETERS ARE SHOWN FOR ROGERS RO4350 WITH THICKNESS .008" $\pm$.0015".
COPPER: 1/2 OZ. EACH SIDE.
FOR OTHER MATERIALS TRACE WIDTH & GAP MAY NEED TO BE MODIFIED.



2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

 DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)

 DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input*	10W max. at 25°C

RF IN	1
RF OUT	3
GROUND	2,4



A	3.20	B	1.60	C	0.95
D	0.51	E	0.81	F	0.23
G	4.29	H	2.21	J	0.61
K	3.10	L	0.61	M	2.21
N	0.30	P	1.80	wt	0.02g

Tel : +86 0755-27881106
Fax : +86 0755-27597069
Add : 806 Building B7, Tianrui Industrial Park, Fuyong Street, Baoan District, Shenzhen

JY-LFCN-180+