







- Notes 1 Lead CO-PLANARITY shall be 0.1mm max.
2 Embossed carrier tape packaging shall be applied to this product.
See next page for details.
3 For modification, etc., preventive hole for sink mark may be added
according to circumstances.
4 The dimensions in parentheses are for reference.

2	PHOSPHOR BRONZE	Contact area : Gold 0.1μm min.		4	POLYESTER	(Top cover tape)		
		Lead area : Gold flash						
		Under plating : Nickel 1μm min.						
1	PPS	Light brown (UL94V-0)		3	POLYSTYRENE	(Embossed carrier tape)		
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS		
UNITS mm		SCALE 5 : 1		COUNT 1	DESCRIPTION OF REVISIONS DIS-F-00006410	DESIGNED KS. NAKAJIMA	CHECKED HT. YAMAGUCHI	DATE 20200803
 HIROSE ELECTRIC CO., LTD.	APPROVED : HS. OKAWA		20060404		DRAWING NO. EDC-150989-92-22			
	CHECKED : HS. OZAWA		20060404		PART NO. FX8-40P-SV(92)			
	DESIGNED : TK. YANAGISAWA		20060403		CODE NO. CL578-0009-8-92			
	DRAWN : TK. YANAGISAWA		20060403		 			

Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.





Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

【Precaution】

When a board with multiple connectors mounted is mated, the connector may be damaged or deformed.
Please divide one side of the board so only one connector is mated per board.

OK

NG



HRS

DRAWING NO.	EDC-150989-92-22
PART NO.	FX8-40P-SV(92)
CODE NO.	CL578-0009-8-92