



Power Double Lock

TE Internal #: 5-316768-1  
Housing, Plug, Wire-to-Wire, 1 Position, 3.96 mm [.156 in]  
Centerline, Wire & Cable, UL 94V-0, Power Double Lock,  
Rectangular Power Connectors

[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > Glow Wire Power Double Lock Plug



Rectangular Power Connector Type: **Housing**  
Connector & Housing Type: **Plug**  
Connector System: **Wire-to-Wire**  
Number of Positions: **1**  
Centerline (Pitch): **3.96 mm [.156 in]**

[All Glow Wire Power Double Lock Plug \(55\)](#)

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	1
Number of Power Positions	1
Number of Signal Positions	0
Number of Rows	1

Electrical Characteristics

Operating Voltage	300 VAC
-------------------	---------



Contact Features

Contact Retention Within Housing	Without
Contact Type	Receptacle

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

Housing Features

Centerline (Pitch)	3.96 mm [.156 in]
Housing Color	Natural
Housing Material	Nylon 6/6

Usage Conditions

Operating Temperature Range	-30 – 105 °C [-22 – 221 °F]
-----------------------------	-----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	GWT 750°C (Without Flame)

Packaging Features

Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.



Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-P87024-R2435  
Power Double Lock Receptacle



TE Part # CAT-P87024-T111  
Power Double Lock Tab



TE Part # 316769-1  
POWER D/LOCK CAP HSG 1P  
NATURA



TE Part # 316770-1  
AMP POWER DBL LOCK 1P PLATE

Also in the Series | Power Double Lock



Connector Contacts(24)



Connector Hardware(14)



Insertion & Extraction Tools(2)



Rectangular Power Connectors(283)

Customers Also Bought



TE Part #2005247-1  
PDL 2P PLUG 3.96(GWT) NAT



TE Part #917728-1  
2.5 SIGNAL D/LOCK HDR ASSY 8P



TE Part #316770-1  
AMP POWER DBL LOCK 1P PLATE



TE Part #917724-1  
2.5 S.D.LOCK HDR ASSY 4P H/PRO





TE Part #2232112-1  
250 FASTON,REC.,18-14 AWG,TPBR



TE Part #5-316769-1  
POWER D/LOCK CAP HSG 1P  
NATURA(GWT)



TE Part #917731-1  
2.5 S.D.L P.HDR ASY 11P H/PRO.



TE Part #60766-2  
SHUR PLUG .156 18-14 AWG PTPBR



TE Part #917732-1  
2.5 SIGNAL D/LOCK HDR ASSY 12P



TE Part #917729-1  
2.5 SIGNAL D/LOCK HDR ASSY 9P

Documents

Product Drawings

POWER DBL LOCK PLUG HSG 1P(GWT)

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_5-316768-1\_E.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_5-316768-1\_E.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_5-316768-1\_E.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

English

AMP POWER DOUBLELOCK CONNECTOR SERIES

English

5-316768-1

Housing, Plug, Wire-to-Wire, 1 Position, 3.96 mm [.156 in] Centerline, Wire & Cable,  
UL 94V-0, Power Double Lock, Rectangular Power Connectors

