# 6-1718321-3 ACTIVE

#### AMP | LEAVYSEAL

TE Internal #: 6-1718321-3

Housing for Female Terminals, Wire-to-Wire, 39 Position, 5 mm [.

197 in] Centerline, Sealable, Brown, Wire & Cable, Power,

LEAVYSEAL

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > LEAVYSEAL Connector Housings











Connector System: Wire-to-Wire

Number of Positions: 39

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 5 mm [ .197 in ]

Sealable: Yes

All LEAVYSEAL Connector Housings (64)

#### **Features**

#### **Product Type Features**

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	39
Number of Rows	3
Electrical Characteristics	
Operating Voltage	36 VDC



#### **Body Features**

Cable Exit Angle	90°
Primary Product Color	Brown
Connector & Keying Code	F

#### **Contact Features**

Contact Size	2.8mm
Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Contact Current Rating (Max)	32 A

#### Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	With
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

#### **Housing Features**

Housing Material	PBT GF20
Centerline (Pitch)	5 mm[.197 in]

#### **Dimensions**

Connector Height	46 mm[1.81 in]
Product Width	44 mm[1.73 in]
Product Length	120.5 mm[4.74 in]
Row-to-Row Spacing	5.5 mm[.216 in]

### **Usage Conditions**

Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]

### Operation/Application

Circuit Application	Power	
Industry Standards		

Degree of Protection	IP67, IP69K
UL Flammability Rating	UL 94V-0

### Packaging Features



Packaging Quantity	1
Packaging Method	Package
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

#### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts

Housing for Female Terminals, Wire-to-Wire, 39 Position, 5 mm [.197 in] Centerline, Sealable, Brown, Wire & Cable, Power, LEAVYSEAL





TE Part # 828905-1 SINGLE-WIRE-SEAL(5MM HOLE)









## Also in the Series | LEAVYSEAL









Other Automotive Connector Accessories(15)



# Customers Also Bought





















#### **Documents**

#### **Product Drawings**

AMP MCP2.8 RECEPTACLE HSG.,39P

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_6-1718321-3\_D\_c-6-1718321-3-d.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6-1718321-3\_D\_c-6-1718321-3-d.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_6-1718321-3\_D\_c-6-1718321-3-d.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

#### Datasheets & Catalog Pages

**LEAVYSEAL CONNECTORS** 

English

ICT Terminals and Connectors Catalogue

English

#### **Product Specifications**

**Application Specification** 

German

Housing for Female Terminals, Wire-to-Wire, 39 Position, 5 mm [.197 in] Centerline, Sealable, Brown, Wire & Cable, Power, LEAVYSEAL

