



- NOTES:
1. ALL PARTS TO BE BULK PACKED.
 2. CONTACTS ASSEMBLED INTO CONNECTOR.
 3. ALL DIMENSIONS ARE REFERENCE ONLY EXCEPT WHERE NOTED WITH A TOLERANCE. DIMENSIONS IN BRACKETS [] ARE METRIC.
 4. PC TAIL LENGTH OPTIONS:
 - STANDARD (SHORT) TAIL = 0.114in [W4281-1XPG-300]
 - INTERMEDIATE = 0.202in [W4291-1XPG-300]
 - LONG = 0.257in [W4292-1XPG-300]

ASS'Y P/N	CONTACTS	HOLE POS. CLOSED
W4292-10PG-300	10 - #20	11, 12
W4292-11PG-300	11 - #20	12
W4292-12PG-300	12 - #20	NONE
W4292-1XPG-300		


NO. OF CONTACTS





MATING VIEW
W4292-10PG-300
10-POS.




MATING VIEW
W4292-11PG-300
11-POS.



MATING VIEW
W4292-12PG-300
12-POS.




PC TAIL LAYOUT



HEX NUT
MAT'L: UV THERMOPLASTIC,
BLACK

O-RING
MAT'L: RUBBER,
BLACK


13/16-27 UNS-2A
MOD. THREAD




PIN CONTACT
PC TAIL
GOLD PLATED

PANEL INSERT, PIN
MAT'L: UV THERMOPLASTIC,
BLACK

.188 MAX.
[4.8mm]
PANEL THICKNESS



PC TAIL VIEW
W4292-10PG-300 - 10-POS. (11&12 CLOSED)
W4292-11PG-300 - 11-POS. (12 CLOSED)
W4292-12PG-300 - 12-POS. (ALL OPEN)



RECOMMENDED
PANEL CUTOUT
STANDARD MULTI-CON-X

CUSTOMER APPROVAL	
THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION.	
APPROVED BY:	_____
DATE:	_____

A	PAK	09/12/19	DRAWING CREATED AND RELEASED PER DOR 10-2523JS-1		
REV.	INIT.	DATE	DESCRIPTION		
	PAK	10/22/14	ORIG. DRAWN BY:		
			CHECKED BY:		
ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION". UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.			APPROVED BY:	TITLE: PANEL PIN, E-KEY 12-POS., #20 PC TAIL, LONG MULTI-CON-X, WEATHER RESISTANT STANDARD PRODUCT	
ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS.			SCALE NTS	SIZE B	SHEET 1 OF 1
UNLESS OTHERWISE SPECIFIED TOLERANCES: 3 PLACE DECIMALS ±.005 ANGLES ±1° FRACTIONS ±1/16			FILE: W4292-1XPG-300	DIRECTORY: SLW	PART NUMBER: W4292-1XPG-300
= CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX					REV A