


# PX0911/03/P Datasheet

Product Name // Flex Cable Connector PX0911 Series 3  
Contact Plug 13mm-15mm Cable (Yellow Gland)

 [View Product Page](#)



// Product Description:

- Flex Cable Connectors
  - Water and dustproof to IP68 when mated with compatible connector
  - Positive fast-acting locking ring - can be turned with a gloved hand
  - Plug or Socket
  - 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version
  - Screw Terminals
- Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details):
    - PX09 part codes 7mm-15mm diameter
    - PXA9 part codes (large cable version with strain relief clamp) 14mm-22mm diameter
  - Packs of Cable Glands for differing cable diameters available separately (PX0980, PXA980)
  - PX0960/PX0990 Sealing Caps available separately to maintain IP rating of unmated connectors
  - Mate with PX09 or PXA9 Series Flex and Panel Mount Connectors, as appropriate

// General Information:

|                                 |                           |
|---------------------------------|---------------------------|
| Product Display Title:          | Flex Cable Connectors     |
| Product Family:                 | Circular Power Connectors |
| Product Series:                 | 900 Series Buccaneer      |
| Approvals:                      | UL                        |
| Body Material:                  | Polyamide (PA)            |
| Body Material Type:             | Plastic Body              |
| Contact Type:                   | Plug Contact              |
| Coupling Type:                  | Screw                     |
| Current Max:                    | 32A                       |
| Diameter Over Coupling Ring Mm: | 58mm                      |
| Flamability Rating:             | UL94V-0                   |
| Function:                       | Flex Cable Connector      |
| Ip Rating:                      | IP68                      |
| Max Cable Entry Size:           | 15mm                      |
| Min Cable Entry Size:           | 13mm                      |
| Max Contact Accomodation Awg:   | 13AWG                     |
| Min Contact Accomodation Awg:   | 10AWG                     |
| Max Contact Accomodation Mm2:   | 4mm2                      |
| Min Contact Accomodation Mm2:   | 2.6mm2                    |
| Max Operating Temperature:      | +85°C                     |
| Min Operating Temperature:      | -40°C                     |
| Number Of Contacts:             | 3 Contacts                |
| Voltage Max:                    | 600V                      |

// Product PDF Links

-  900 Series power connectors...
-  900 Series power connectors wiring...

// Product 3D CAD Model Links

-  PX0911/03/P3D CAD Model



Have a question or project enquiry  
you'd like to talk to us about?



[Click Here To Contact Us](#)