

Part Number: 5025851576

Product Description: 1.50mm Pitch, CLIK-Mate PCB Receptacle, Single Row, Surface Mount, Right-Angle, Tin Plating, Positive Lock,

15 Circuits, Green

Status: New Business Not Supported

Series Number: 502585

Product Category: PCB Headers and

Receptacles

Documents & Resources

Product Environment Compliance

Compliance

| GADSL/IMDS | Compliant with Exemption 44; 34; 33 |
|--------------------|--|
| China RoHS | • |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | New Business Not Supported |
|----------------|---|
| Category | PCB Headers and Receptacles |
| Series | 502585 |
| Description | 1.50mm Pitch, CLIK-Mate PCB Receptacle, Single Row, Surface Mount, Right-Angle, Tin Plating, Positive Lock, 15 Circuits, Green |
| Application | Signal, Wire-to-Board |
| Component Type | PCB Receptacle |
| Product Family | CLIK-Mate Wire-to-Board Connectors |
| Product Name | CLIK-Mate |
| UPC | 800756778389 |

Agency

| UL | E29179 |
|----|--------|
|----|--------|

Electrical

| Current - Maximum per Contact | 2.0A |
|-------------------------------|------|
| Voltage - Maximum | 100V |

Physical

| Circuits (Loaded) | 15 |
|--------------------------------|--------------|
| Circuits (maximum) | 15 |
| Color - Resin | Green |
| Durability (mating cycles max) | 30 |
| Flammability | SC-0 |
| Glow-Wire Capable | No |
| Guide to Mating Part | Yes |
| Keying to Mating Part | None |
| Lock to Mating Part | Yes |
| Mated Height | 6.40mm |
| Material - Metal | Copper Alloy |
| Material - Plating Mating | Tin |
| Net Weight | 1044.000/mg |
| Number of Rows | 1 |

| Orientation | Right Angle |
|-------------------------------|-----------------------|
| Packaging Type | Embossed Tape on Reel |
| PCB Locator | No |
| PCB Retention | Yes |
| Pitch - Mating Interface | 1.50mm |
| Pitch - Termination Interface | 1.50mm |
| Polarized to Mating Part | Yes |
| Polarized to PCB | No |
| Stackable | No |
| Temperature Range - Operating | -40° to +105°C |
| Termination Interface Style | Surface Mount |

This document was generated on Sep 16, 2024