

1153078

<https://www.phoenixcontact.com/us/products/1153078>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Security-Router, 5 RJ45 ports 10/100/1000 Mbps, NAT, Unmanaged Switch, Stateful inspection firewall

Product description

NAT firewall

Your advantages

- The new Firewall Assistant helps you to create Firewall rules
- High data throughput
- Inexpensive entry into network security
- Test Mode: easily test the created firewall rules without limiting system availability
- Easy Protect Mode: without requiring any configuration, wire bridges are used to block external network access attempts

Commercial data

Item number	1153078
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DN27
Product key	DNN311
GTIN	4063151151713
Weight per piece (including packing)	430.05 g
Weight per piece (excluding packing)	326.81 g
Customs tariff number	85176200
Country of origin	DE

# FL MGUARD 1105 - Router

1153078

<https://www.phoenixcontact.com/us/products/1153078>



## Technical data

### Dimensions

Width	45 mm
Height	130 mm
Depth	130 mm

### Notes

#### Note on application

Note on application	Only for industrial use
---------------------	-------------------------

### Material specifications

Color	gray
Housing material	Polycarbonate fiber reinforced

### Interfaces

#### Ethernet

Connection method	RJ45
Transmission speed	10/100/1000 Mbps
Transmission physics	Ethernet in RJ45 twisted pair
Transmission length	100 m (per segment)
Signal LEDs	Supply voltage, data transmission, error, link, activity
No. of channels	5 (RJ45 ports)

#### Signal contact

Connection method	Push-in-/Spring-cage connection
Additional text	not electrically isolated

### System properties

#### Functionality

Basic functions	NAT firewall with intelligent firewall, slot for SD memory card
-----------------	---

#### System requirements

Supported browsers	Firefox, Chrome, Edge in the latest version
--------------------	---

### Product properties

Product type	Security router for the DIN rail
Product family	Security-Router
Type	Stand-Alone
Special properties	NAT
	Unmanaged Switch

#### Data management status

Article revision	07
------------------	----

# FL MGUARD 1105 - Router



1153078

<https://www.phoenixcontact.com/us/products/1153078>

## Insulation characteristics

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

## Security functions

Filtering	IP, port, protocol
Firewall rules	Stateful inspection firewall
Basic functions	NAT firewall with intelligent firewall, slot for SD memory card
Network Time Protocol (NTP) client	Client/server
Routing	Standard routing, NAT, 1:1-NAT, port forwarding
Protection against	IP spoofing, DoS and Syn Flood Protection

## Electrical properties

Local diagnostics	US1 Supply voltage US1 Green LED
	One LED per port Link active Green LED
Maximum power dissipation for nominal condition	typ. 2.88 W

## Supply

Supply voltage (DC)	24 V DC
Supply voltage range	18 V DC ... 32 V DC
Power supply connection	via COMBICON, max. conductor cross section 1.5 mm <sup>2</sup>
Residual ripple	3.6 V <sub>PP</sub> (within the permitted voltage range)
Max. current consumption	1060 mA (loaded outputs)
Typical current consumption	180 mA (at 24 V DC)

## Function

Signal contact control voltage	24 V DC (typical)
Signal contact control current	250 mA (short-circuit-proof)

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)

## Approvals

### Conformity/Approvals

Conformance	CE-compliant
-------------	--------------

## Mounting

Mounting type	DIN rail mounting
---------------	-------------------

## EMC data

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
-------------------------------	---

# FL MGUARD 1105 - Router



1153078

<https://www.phoenixcontact.com/us/products/1153078>

Conformance with EMC directives	IEC 61000-6-2 IEC 61000-4-2 (ESD) 6 kV contact discharge, 8 kV air discharge
	IEC 61000-6-2 IEC 61000-4-3 (immunity to radiated interference) 10 V/m (80 MHz ... 2000 MHz)
	IEC 61000-6-2 IEC 61000-4-4 (burst) 2 kV power line, 1kV data line
	IEC 61000-6-2 IEC 61000-4-5 (surge) power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
	IEC 61000-6-2 IEC 61000-4-6 (immunity to conducted interference) 3 V (10 kHz ... 150 kHz), 10 V (150 kHz ... 80 MHz)
Noise immunity	EN 61000-6-2:2005
Noise emission	EN 55022 / Class B

## Signaling

Status display	Supply voltage, data transmission, error, link, activity
----------------	--

# FL MGUARD 1105 - Router

1153078

<https://www.phoenixcontact.com/us/products/1153078>



## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1153078>



**cUL Listed**

Approval ID: E238705



**cULus Listed**

Approval ID: E366272

# FL MGUARD 1105 - Router



1153078

<https://www.phoenixcontact.com/us/products/1153078>

## Classifications

### ECLASS

ECLASS-11.0	19170406
ECLASS-12.0	19170406
ECLASS-13.0	19170406

### ETIM

ETIM 9.0	EC001478
----------	----------

### UNSPSC

UNSPSC 21.0	43222600
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	4,4'-isopropylidenediphenol(CAS: 80-05-7)
	Lead(CAS: 7439-92-1)
SCIP	52442c30-d6e6-446e-af75-7c6c01d79249