




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.32 – .82 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

|                 |        |
|-----------------|--------|
| Insertion Force | Normal |
|-----------------|--------|

Configuration Features

|                                   |               |
|-----------------------------------|---------------|
| Connection Capacity               | Single        |
| Compatible With Wire & Cable Type | Discrete Wire |

Contact Features

|                                |                 |
|--------------------------------|-----------------|
| Quick Disconnect Terminal Type | Tab             |
| Mating Tab Width               | 2.8 mm[.11 in]  |
| Mating Tab Thickness           | .81 mm[.032 in] |
| Terminal Orientation           | Straight        |
| Contact Base Material          | Brass           |
| Terminal Plating Material      | Tin             |
| Crimp Type                     | F-Crimp         |
| Barrel Type                    | Open            |

Termination Features

|  |  |
|--|--|
|  |  |
|--|--|



|                       |              |
|-----------------------|--------------|
| Product Terminates To | Wire & Cable |
|-----------------------|--------------|

Mechanical Attachment

|                         |        |
|-------------------------|--------|
| Wire Insulation Support | With   |
| Mating Retention Type   | Dimple |

Dimensions

|                                      |                             |
|--------------------------------------|-----------------------------|
| Terminal Material Thickness          | .41 mm[.016 in]             |
| Product Length                       | 19.05 mm[.75 in]            |
| Compatible Insulation Diameter Range | 2.29 – 3.3 mm[.09 – .13 in] |
| Wire Size                            | .32 – .82 mm²               |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Insulation Option           | Uninsulated                |
| Operating Temperature Range | -40 – 110 °C[-40 – 230 °F] |

Industry Standards

|                                           |    |
|-------------------------------------------|----|
| Compatible With Agency/Standards Products | UL |
|-------------------------------------------|----|

Packaging Features

|                    |            |
|--------------------|------------|
| Packaging Quantity | 4000       |
| Packaging Method   | Strip/Reel |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                             |
| Solder Process Capability                     | Not applicable for solder process capability                                                                                    |

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts

|                                                                    |                                                                  |                                                                  |                                                         |
|--------------------------------------------------------------------|------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------|
| <br>TE Part # 60794-2<br>FASTIN NECESSARY?? - separate<br>GPL: 326 | <br>TE Part # 63138-1<br>110 FASTON REC 22-18 AWG TPBR           | <br>TE Part # 42475-4<br>250 FASTON TAB 22-18 AWG TPBR           | <br>TE Part # 61281-3<br>250 FASTON TAB 14-12 AWG TPBR  |
| <br>TE Part # 42770-2<br>250 FASTON FLAG TAB 18-14 AWG<br>TPBR     | <br>TE Part # 63932-1<br>110 FASTON TAB 22-18 AWG TPBR           | <br>TE Part # 1494210-2<br>110 FASTON,TAB,22-17 AWG, JIS<br>C260 | <br>TE Part # 1742753-1<br>FASTON 2MM TAB 18-22AWG TPBR |
| <br>TE Part # 42475-2<br>250 FASTON TAB 22-18 AWG TPBR             | <br>TE Part # 1494210-1<br>110 FASTON,TAB,22-17 AWG, JIS<br>C260 | <br>TE Part # 42475-3<br>250 FASTON TAB 22-18 AWG BR             | <br>TE Part # 180353-2<br>250 FASTON,TAB,12-10 AWG,TPBR |
| <br>TE Part # 63535-1<br>TAB SPECIAL 025TPBR                       | <br>TE Part # 680076-4<br>HDM 9SMPR090F G                        |                                                                  |                                                         |






Also in the Series | **FASTON 250**

|                                                                                                                    |                                                                                                                        |                                                                                                                                |                                                                                                                     |
|--------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
|  <p>Compression Connectors(4)</p> |  <p>Crimp Terminal Housings(132)</p> |  <p>Insertion &amp; Extraction Tools(6)</p> |  <p>Magnet Wire Terminals(1)</p> |
|  <p>PCB Terminals(134)</p>       |  <p>Quick Disconnects(426)</p>      |  <p>Splices(4)</p>                         |                                                                                                                     |

Customers Also Bought

|                                                                                                                                                  |                                                                                                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
|  <p>TE Part #5103308-1<br/>A/L LOW PRO HDR 10P VERT BLACK</p> |  <p>TE Part #640418-2<br/>BLADE REC 250 18-14AWG TPBR</p> |
|--------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|

Documents

Product Drawings  
FASTON 110 AMPLIVAR TAB 23-19 MAG TPBR

English

CAD Files  
3D PDF  
3D  
Customer View Model  
ENG\_CVM\_CVM\_63165-2\_AB.2d\_dxf.zip  
English  
Customer View Model  
ENG\_CVM\_CVM\_63165-2\_AB.3d\_igs.zip  
English  
Customer View Model  
ENG\_CVM\_CVM\_63165-2\_AB.3d\_stp.zip



English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.