

EV-T2M3PC-3AC32A-4,0M6,0EHBK00 - AC charging cable



1622495
<https://www.phoenixcontact.com/us/products/1622495>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

CHARX connect, Mobile AC charging cable with vehicle connector and infrastructure plug, with protective cap, Type 2, IEC 62196-2, cable: 4 m, spiraled



Product description

Mobile AC charging cable with vehicle charging connector and infrastructure charging plug for charging electric vehicles (EV) with alternating current (AC) via type 2 vehicle charging inlets, compatible with type 2 infrastructure charging sockets at charging stations for e-mobility (EVSE)

Your advantages

- Consistent design of all Phoenix Contact Vehicle Connectors and Infrastructure Plugs
- Silver-plated surface of the power and signal contacts
- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- Convenient handling, thanks to the ergonomic handle and additional, rubber grip components

Commercial data

Item number	1622495
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	XWBAEC
Catalog page	Page 748 (C-2-2017)
GTIN	4055626044064
Weight per piece (including packing)	4.58 kg
Weight per piece (excluding packing)	4.49 kg
Country of origin	DE

EV-T2M3PC-3AC32A-4,0M6,0EHBK00 - AC charging cable



1622495

<https://www.phoenixcontact.com/us/products/1622495>

Technical data

Product properties

Product type	AC charging cable
Product family	CHARX connect
Application	Mobile AC charging cable with vehicle connector and infrastructure plug, with protective cap
Charging mode	Mode 3, Case B
Charging standard	Type 2

Electrical properties

Type of charging current	AC 3-phase
Charging power	26.6 kW
Charging current	32 A

Cable/line

Cable length	4 m
Wiring standards/regulations	prEN 50620/DIN EN 50620
Wiring certifications	VDE
Cable type	Class 5
Cable type	spiraled
Cable structure	5 x 6.0 mm ² + 1 x 0.5 mm ²
External cable diameter	17.00 mm ±0.4 mm
Outer sheath, material	TPE-U
Block length	0.63 m ±10 %
Coil diameter	80 mm ±10 %
Effective length	max. 4 m ±5 %
Cable resistance	≤ 0.0033 Ω/m (based on a power core, at an ambient temperature of 20°C)
Bending radius	min. 102 mm (6x diameter)
Cable length	4 m
External cable diameter	17.00 mm ±0.4 mm
Cable type	Class 5
Wiring certifications	VDE
Wiring standards/regulations	prEN 50620/DIN EN 50620
Cable resistance	≤ 0.0033 Ω/m (based on a power core, at an ambient temperature of 20°C)

Standards and regulations

Standards

Standards/regulations	IEC 62196-2
-----------------------	-------------

EV-T2M3PC-3AC32A-4,0M6,0EHBK00 - AC charging cable




1622495

<https://www.phoenixcontact.com/us/products/1622495>


Drawings

Schematic diagram



Pin assignment of the Vehicle Connector

Connection diagram



Pin assignment of Infrastructure Plug


EV-T2M3PC-3AC32A-4,0M6,0EHBK00 - AC charging cable



1622495


<https://www.phoenixcontact.com/us/products/1622495>

Schematic diagram



Operating instructions

Dimensional drawing




Vehicle connector

EV-T2M3PC-3AC32A-4,0M6,0EHBK00 - AC charging cable



1622495

<https://www.phoenixcontact.com/us/products/1622495>



Infrastructure plug

EV-T2M3PC-3AC32A-4,0M6,0EHBK00 - AC charging cable



1622495
<https://www.phoenixcontact.com/us/products/1622495>

Classifications

UNSPSC

UNSPSC 21.0	39121522
-------------	----------

EV-T2M3PC-3AC32A-4,0M6,0EHBK00 - AC charging cable



1622495
<https://www.phoenixcontact.com/us/products/1622495>

Environmental product compliance

China RoHS	
Environment friendly use period (EFUP)	<div>EFUP-10</div> <div>An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.</div>
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

EV-T2M3PC-3AC32A-4,0M6,0EHBK00 - AC charging cable



1622495

<https://www.phoenixcontact.com/us/products/1622495>

Accessories

EV-T2AC-PARK - Charging connector holder

1624148

<https://www.phoenixcontact.com/us/products/1624148>



CHARX connect, Charging connector holder, Accessories, for vehicle charging connectors on charging stations (EVSE), Type 2, IEC 62196-2, Front mounting, housing: black, PHOENIX CONTACT logo

EV-T2M3SE24-3AC32A-0,7M6,0E10 - Infrastructure charging socket

1405216

<https://www.phoenixcontact.com/us/products/1405216>



CHARX connect, Infrastructure charging socket, for charging electric vehicles (EV) with alternating current (AC), Type 2, IEC 62196-2, 32 A / 480 V (AC), Single wires, length: 0.7 m, locking actuator: 24 V, 4-pos., Rear panel mounting, PHOENIX CONTACT logo

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com