

# VARISTAR MIL 901D, with elastomer shock absorbers, EMC shielded

SCHROFF



Elastomer shock absorbers

Other Views



Catalog Number: 10130-201

Back To Product

- Cabinet (IP 55) for extreme seismic and mobile conditions (with shock absorbers)
- Tested to MIL-STD-901D
- Doubly protected against corrosion, zinc-plated and powder-coated
- 4 shock absorbers at bottom and 2 shock absorbers at top
- EMC protection 60 dB at 1 GHz, 40 dB at 3 GHz (IEC 61587-3)
- Rear panel horizontally partitioned for fitting of e.g. cable ducting

Product family:

Varistar

Degree of protection:

IP 55 or NEMA 12

Shielding:

Yes

Type:

Floor-standing cabinet

Load:

400 kg/ 880 lb static

Dynamic Load:

150 kg dynamic

Certification:

MIL 901D

Delivery Includes:

assembled

Note:

Other dimensions and versions on request



Select product specifications before modifying or adding to project list or requesting a quote.

Configuration-defining

With elastomer schock absorber:





[Clear Selection](#)

Quantity


Modify Product ▶

Add Item to Project List +

Documents

- Main Catalog - Varistar MIL
- EMC test - 1 GHz
- EMC Test 3 GHz (English)
- Shock and vibration test to IEC 61 587-1 (DL6)

Links

- Test report

## Technical Data

Depth mm	800.0
Height mm	1800.0
Width mm	600.0
Depth D mm	800.0
Description	With elastomer shock absorbers
Shielding at 1 GHz	60 dB
Height U	38

Delivery Comprises:

Item	Quantity	Description
1	1	Welded basic frame, heavy duty, St profile, RAL 7032, with reinforcement brackets welded on floor frame, 10 mm, St, finish AlZn; base plate, St; 4 shock absorbers; EMC gasket
2	1	Flat top cover, flush, St, finish AlZn, exterior RAL 7032
3	1	Front door, St, finish AlZn, RAL 7032, 180° hinge, 4-point locking, lever handle
4	1	Rear panel, top, screw fixed, St, finish AlZn, RAL 7032; 2 shock absorbers;
5	1	Rear panel, centre, screw fixed, St, finish AlZn, RAL 7032
6	1	Rear panel, bottom, screw fixed, St, finish AlZn, RAL 7032
7	2	Side panel, screw fixed, St, AlZn, RAL 7032
8	4	19" panel/slide mount with EIA perforation, St, finish AlZn, depth-adjustable in 25 mm increments
9	1	GND/earthing kit, assembled

Accessories

EXPLORE	CONTACT	DOWNLOAD
About Us	Customer Service	Download Center
Services & Capabilities	Find a Sales Office or Distributor	Reference Projects
News & Events	Global Locations	Videos
Newsletter Subscriptions	Product Compliance & Certifications	Product Configurators
Strategic Partnerships	Partner Login	Warranties and Terms of Sale & Procurement
Investor Relations		

© 2018 nVent. All rights reserved | [Privacy Policy](#) | [Terms of Use](#) | [Cookie Policy](#) | [Imprint](#) | [Site Map](#)

Connect With Us

