



Connectors > Terminal Blocks & Strips > PCB Terminal Blocks



Terminal Block Connector Type: **Plug**  
Connector System: **Wire-to-Board**  
Number of Positions: **3**  
Centerline (Pitch): **5.08 mm [.2 in]**  
Number of Rows: **1**

Features

Product Type Features

|                                   |               |
|-----------------------------------|---------------|
| Wire Protection                   | With          |
| Terminal Block Connector Type     | Plug          |
| Connector System                  | Wire-to-Board |
| Connector & Contact Terminates To | Wire & Cable  |

Configuration Features

|                        |                |
|------------------------|----------------|
| Wire Entry Location    | Top            |
| Stacking Configuration | Side Stackable |
| Number of Positions    | 3              |
| Number of Rows         | 1              |
| Wire Entry Angle       | 180°           |

Electrical Characteristics

|                   |         |
|-------------------|---------|
| Operating Voltage | 300 VAC |
|-------------------|---------|

Body Features

|                       |       |
|-----------------------|-------|
| Primary Product Color | Green |
|-----------------------|-------|



|                                                                 |                                                                                                                                 |
|-----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Product Orientation                                             | Vertical                                                                                                                        |
| Contact Features                                                |                                                                                                                                 |
| Contact Mating Area Plating Material                            | Tin                                                                                                                             |
| Contact Base Material                                           | Phosphor Bronze                                                                                                                 |
| Contact Current Rating (Max)                                    | 16 A                                                                                                                            |
| Mechanical Attachment                                           |                                                                                                                                 |
| Screw Plating Material                                          | Zinc                                                                                                                            |
| Screw Material                                                  | Steel                                                                                                                           |
| Housing Features                                                |                                                                                                                                 |
| Housing Material                                                | PA 66                                                                                                                           |
| Centerline (Pitch)                                              | 5.08 mm[.2 in]                                                                                                                  |
| Dimensions                                                      |                                                                                                                                 |
| Wire Size                                                       | .2 – 2 mm²                                                                                                                      |
| Usage Conditions                                                |                                                                                                                                 |
| Operating Temperature Range                                     | -40 – 105 °C[-40 – 221 °F]                                                                                                      |
| Operation/Application                                           |                                                                                                                                 |
| Circuit Application                                             | Power & Signal                                                                                                                  |
| Packaging Features                                              |                                                                                                                                 |
| Packaging Quantity                                              | 400                                                                                                                             |
| Packaging Method                                                | Bag                                                                                                                             |
| Product Compliance                                              |                                                                                                                                 |
| For compliance documentation, visit the product page on TE.com> |                                                                                                                                 |
| EU RoHS Directive 2011/65/EU                                    | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                                     | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016                   | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006                          | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                                                 | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                             |



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2350513-3  
3POS TB HDR 90 DEG, PITCH 5.0 & TL 4.5mm

Customers Also Bought

TE Part #5747190-1  
09 RCPT SP/MS CNUT

TE Part #5747844-3  
09 MSFL RCPT RA 318 (IN,FM,BL)

TE Part #5-102202-2  
05 MODII HDR SRST SHRD LF

TE Part #5-103166-1  
06 MODII HDR DRRA SHRD LF

TE Part #1-770186-1  
12P MINI UMNL ASSY VO SNAU LF

TE Part #535032-4  
096 EURO TYPE C RECEPT AP ASSY

TE Part #1658998-1  
Mini DIN, 8 pos, R/A, Shield

TE Part #5-66461-4  
SKT,.062 DIA,.025 SQ POST,LP





Documents

Product Drawings

Plug, 5.08mm, Gn, Ss & WE same side, 3p

English

CAD Files

Customer View Model

ENG\_CVM\_CVM\_1986484-3\_A.2d\_dxf.zip

English

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1986484-3\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1986484-3\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

1-1773458-1\_EURO\_STYLE\_TERMINAL\_BLOCKS\_QRG

English