











mat'l. code			surface		tolerance		projection		product family	
			ISO 1302		ISO 406 ISO				MINITEK127®	
ltr	ecm no	dr	date		tolerances unless otherwise specified		mm		title	
M	EX-N-2544	TONY	07/21/16		angles .0±.30				RECEPTACLE VT SMT	
N	EX-N-26833	TONY	03/14/17		linear .00±.20					
P	EX-N-29534	TONY	03/13/18		0°±.2° .000±.10		scale 1:1		dwg no	
			dr		Tony Leng 07/19/16				sheet 1 of 4 size	
			engr		Tony Leng 07/19/16				20021321 A3	
			chr		ZK Hu 07/19/16					
					qppd		Tim Yoo 07/19/16		type Product Customer Drawing	
sheet index	revision	P								
sheet index	sheet	1								



P/N: 20021321-X0108XXLF









P/N: 20021321-X0214XXLF/20021321-X0206XXLF

P/N: 20021321-X0312XXLF

TABLE 3

DASH NO.	AMOUNT OF PINS	PIN FILLED
-X0108XXLF	7	PIN #4
-X0214XXLF	13	PIN #2
-X0206XXLF	5	PIN #2
-X0312XXLF	11	PIN #7

mat'l. code				surface		tolerance		projection		product family	
ltr	ecn	no	dr	date	ISO 1302	ISO 406	ISO 1104	1104	1104	MINITEK127®	title
					tolerances unless otherwise specified						RECEPTACLE VT SMT
					angles		.0±.30				
					linear		.00±.20		mm		
					0±2°		.000±.10		scale 1:1		
					dr	Tony Leng	07/19/16				dwg no
					engr	Tony Leng	07/19/16				sheet 2 of 4
					chr	ZK Hu	07/19/16				size
					qppd	Tim Yoo	07/19/16				A3
sheet	revision	P									type
index	sheet	2									Product Customer Drawing



mat'l. code		surface ✓ tolerance			projection		product family	
		ISO 1302	✓	ISO 406 ISO	110° φ — mm		MINITEK127®	
ltr	ecn no	dr	date	tolerances unless otherwise specified		title		
				angles		RECEPTACLE VT SMT		
				linear	.0±.30			
					.00±.20			
				0±.2°	.000±.10			
				scale 1:1				
				dr	Tony Leng	07/19/16	dwg no	
				engr	Tony Leng	07/19/16	sheet 3 of 4	
				chr	ZK Hu	07/19/16	20021321	
				appd	Tim Yao	07/19/16	size	
sheet	revision	P				type		Product Customer Drawing
index	sheet	3						

TABLE 1

PRODUCT NO.	POSITIONS	DIM. A	DIM. B
20021321-X0X06XXLF	2 X 3	2.54	4.27
20021321-X0X08XXLF	2 X 4	3.81	5.54
20021321-X0X10XXLF	2 X 5	5.08	6.81
20021321-X0X12XXLF	2 X 6	6.35	8.08
20021321-X0X14XXLF	2 X 7	7.62	9.35
20021321-X0X16XXLF	2 X 8	8.89	10.62
20021321-X0X18XXLF	2 X 9	10.16	11.89
20021321-X0X20XXLF	2 X 10	11.43	13.16
20021321-X0X22XXLF	2 X 11	12.7	14.43
20021321-X0X24XXLF	2 X 12	13.97	15.7
20021321-X0X26XXLF	2 X 13	15.24	16.97
20021321-X0X28XXLF	2 X 14	16.51	18.24
20021321-X0X30XXLF	2 X 15	17.78	19.51
20021321-X0X32XXLF	2 X 16	19.05	20.78
20021321-X0X34XXLF	2 X 17	20.32	22.05
20021321-X0X36XXLF	2 X 18	21.59	23.32
20021321-X0X38XXLF	2 X 19	22.86	24.59
20021321-X0X40XXLF	2 X 20	24.13	25.86
20021321-X0X42XXLF	2 X 21	25.4	27.13
20021321-X0X44XXLF	2 X 22	26.67	28.4
20021321-X0X46XXLF	2 X 23	27.94	29.67
20021321-X0X48XXLF	2 X 24	29.21	30.94
20021321-X0X50XXLF	2 X 25	30.48	32.21
20021321-X0X52XXLF	2 X 26	31.75	33.48
20021321-X0X54XXLF	2 X 27	33.02	34.75
20021321-X0X56XXLF	2 X 28	34.29	36.02
20021321-X0X58XXLF	2 X 29	35.56	37.29
20021321-X0X60XXLF	2 X 30	36.83	38.56
20021321-X0X62XXLF	2 X 31	38.1	39.83
20021321-X0X64XXLF	2 X 32	39.37	41.1
20021321-X0X66XXLF	2 X 33	40.64	42.37
20021321-X0X68XXLF	2 X 34	41.91	43.64


PRODUCT NO.	POSITIONS	DIM. A	DIM. B
20021321-X0X70XXLF	2 X 35	43.18	44.91
20021321-X0X72XXLF	2 X 36	44.45	46.18
20021321-X0X74XXLF	2 X 37	45.72	47.45
20021321-X0X76XXLF	2 X 38	46.99	48.72
20021321-X0X78XXLF	2 X 39	48.26	49.99
20021321-X0X80XXLF	2 X 40	49.53	51.26
20021321-X0X82XXLF	2 X 41	50.8	52.53
20021321-X0X84XXLF	2 X 42	52.07	53.8
20021321-X0X86XXLF	2 X 43	53.34	55.07
20021321-X0X88XXLF	2 X 44	54.61	56.34
20021321-X0X90XXLF	2 X 45	55.88	57.61
20021321-X0X92XXLF	2 X 46	57.15	58.88
20021321-X0X94XXLF	2 X 47	58.42	60.15
20021321-X0X96XXLF	2 X 48	59.69	61.42
20021321-X0X98XXLF	2 X 49	60.96	62.69
20021321-X0XA0XXLF	2 X 50	62.23	63.96

NOTES:

1. MATERIAL:
HOUSING: HIGH TEMPERATURE PLASTIC; UL 94-V0; BLACK.
TERMINAL: PHOSPHOR BRONZE.
CAP: STAINLESS STEEL.
2. FINISH:
TERMINAL: GOLD OR GXT PLATING AT CONTACT AREA (SEE TABLE);
GOLD FLASH OR 2.54um/100u" MIN MATTE TIN
AT SOLDER TAIL AREA;
127um/50u" MIN NI OVER ALL AS UNDERPLATING.
3. PRODUCT SPEC PER GS-12-629.
4. PACKAGE SPEC PER GS-14-1420.
5. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A CONVECTION INFRARED OR VAPOR PHASE REFLOW OVEN.
6. PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
7. THE METAL CAP IS OPTION AS CUSTOMER REQUIREMENT.

PART NUMBER DESCRIPTION:

20021321 - X 0 X X X X X X LF



mat'l. code		surface	tolerance	projection	product family	
ltr	ecn no	dr	date	ISO 1302	ISO 406	ISO 1101
				tolerances unless otherwise specified		
			angles	linear	0±.30	mm
			0±2°	linear	.00±.20	mm
			0±2°	linear	.000±.10	mm
			dr	Tony Leng	07/19/16	
			engr	Tony Leng	07/19/16	
			chr	ZK Hu	07/19/16	
			pppd	Tim Yoo	07/19/16	
sheet	revision	P				
index	sheet	4				

MINITEX127®

RECEPTACLE VT SMT

dwg no sheet 4 of 4 size

20021321

type Product Customer Drawing