

1420372

https://www.phoenixcontact.com/us/products/1420372

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 5-position, Socket, straight, M12-SPEEDCON, coding: A, on free cable end, Rear mounting, Pg9, Individual wires, cable length: 2 m, 0.50 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1239298

Commercial data

Item number	1420372
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB24
Product key	ABQCHE
GTIN	4055626316208
Weight per piece (including packing)	87.4 g
Weight per piece (excluding packing)	76.25 g
Customs tariff number	85444290
Country of origin	DE



1420372

https://www.phoenixcontact.com/us/products/1420372

Technical data

Notes

0.63	
Order information:	Lock nut is included in the scope of delivery
General	Contact connection method: Crimp connection
Safety note	
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	 WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
	 WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
	 The products are suitable for applications in plant, controller, and electrical device engineering.
	 When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
	 Assembled products may not be manipulated or improperly opened.
	 Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
	 When using the product in direct connection with third-party manufacturers, the user is responsible.
	 For operating voltages > 50 V AC, conductive connector housings must be grounded
	 Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.
	Observe the corresponding technical data. You will find information: o On the product o On the packing label o In the supplied documentation o Online at phoenixcontact.com/products under the product
	Only use tools recommended by Phoenix Contact
	 Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products
	 Ensure that the protective or functional ground has been properly connected.
	 VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or



1420372

https://www.phoenixcontact.com/us/products/1420372

connector
 The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).
Rear mounting Pg9
0
Circular connectors (device side)
5
1
A
M12
09
II
3
1.5 kV AC
60 V
4 A
Individual wires
Socket
0.5 mm²
2 Nm 3 Nm
Socket
straight
M12 SPEEDCON



1420372

https://www.phoenixcontact.com/us/products/1420372

Connection 2	ction 2		
Head design	free cable end		
Cable/line			
Cable length	2 m		
Cable cross section	0.5 mm²		
Environmental and real-life conditions Ambient conditions			
Ambient conditions			
	IP67 (When plugged in)		
Ambient conditions	IP67 (When plugged in) IP65 (When plugged in)		
Ambient conditions			
Ambient conditions Degree of protection	IP65 (When plugged in)		



1420372

https://www.phoenixcontact.com/us/products/1420372

Classifications

ECLASS

UNSPSC 21.0

	ECLASS-11.0	27440102	
	ECLASS-12.0	27440116	
	ECLASS-13.0	27440116	
ETIM			
	ETIM 9.0	EC002635	
UN	SPSC		

39121400



1420372

https://www.phoenixcontact.com/us/products/1420372

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	2c5f5e31-8f2b-4fcf-bc47-8a3b76269de6

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com