

# Actuator

704.413.010

Distribution by DigiKey







## Your product:



## 704.413.010 Actuator

	_	_		-
ь.	к	()	N	

Front bezel colour: Black

Front bezel material: Aluminium

Front dimension: Ø 35 mm

#### **MOUNTING**

**Mounting cut-out:** Ø 30.5 mm

Design: flush

### **OPERATING-/INDICATION PART**

Lever material: plastic

Lever shape: short

Lever colour: Black

## **ELECTRICAL CHARACTERISTICS**

Standards: The switches comply with the "Standards for low-voltage switching devices" DIN

EN 60947-1

### **MECHANICAL CHARATERISTIC**

**Switching positions:** 2 positions

**Mechanical lifetime:** ≤2.5 Mio. cycles of operation

**Switching action:** Rest - Momentary

**Weight:** 0.056 kg

**Switching angle:** 42° right

#### **AMBIENT CONDITION**

Storage temperature:  $-40 \,^{\circ}\text{C} \dots + 85 \,^{\circ}\text{C}$ 

**IP Protection:** IP65 front side

**Operating temperature:**  $-40 \, ^{\circ}\text{C} \, ... + 55 \, ^{\circ}\text{C}$ 

#### **OTHER**

Hints: Max. 3 switching elements can be clipped on

Short Description: Actuator, Ø 30.5 mm, Ø 35 mm, non illuminative, Black, short, Black, Aluminium,


anodised, Rest - Momentary

max. number of switching

elements:

3

**Dimension drawings:** 




A = Screw terminal


Wiring diagrams:



**Switching positions:** 



## Mounting cut-outs:



A = Screw terminal B = Push-in terminal (PIT) C = Plug-in terminal 6.3 mm x 0.8 mm D = Double plug-in terminal 6.3 mm x 0.8