

SPECIFICATION CONTROL DRAWING		55PC0232	
TITLE		THREE CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, 600 VOLT	Date
		12-6-96	Revision
		C	

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

COMPONENT WIRES - 55PC0212



CONSTRUCTION DETAILS						
PART NUMBER	CONDUCTOR SIZE (AWG)	DIAMETER (in.)		WEIGHT (lbs/1000 ft.)		
		LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	
55PC0232-24.*	24	.081	.085	.089	6.02	6.30
55PC0232-22.*	22	.094	.098	.102	8.82	9.13
55PC0232-20.*	20	.112	.116	.121	13.32	13.68
55PC0232-18.*	18	.132	.137	.142	20.04	20.66
55PC0232-16.*	16	.148	.153	.158	25.46	26.13
55PC0232-14.*	14	.180	.185	.191	39.17	40.06
55PC0232-12.*	12	.219	.226	.232	60.01	61.19
55PC0232-10.*	10	.269	.278	.287	94.65	96.77
55PC0232-8.*	8	.408	.423	.438	173.	181.
55PC0232-6.*	6	.504	.523	.542	273.	286.
55PC0232-4.*	4	.648	.672	.696	444.	464.

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C
Maximum continuous conductor temperature
VOLTAGE RATING: 600 volts (rms)
INSULATION FLAWS:
Impulse Dielectric Test, 8.0 kV (peak)
PART NUMBER:
The "*" in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors.
Example: AWG 22, red, blue and yellow component wires; 55PC0232-22-2/6/4

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681.

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.