




STRADA

TE Internal #: 5-2143411-1
PCB Mount Receptacle, Vertical, Board-to-Board, 24 / 83 Position,
3.04 mm / 6.09 mm [.12 in / .24 in] Centerline, Gold, Through Hole -
Press-Fit
[View on TE.com >](#)

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Receptacle**
PCB Mount Orientation: **Vertical**
Connector System: **Board-to-Board**
Number of Positions: **24, 83**
Centerline (Pitch): **3.04 mm, 6.09 mm [.12 in, .24 in]**

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Pairs per Column	4
Number of Power Positions	0
Number of Pairs	24
Number of Loaded Positions	83
Stackable	No
Number of Signal Positions	4
PCB Mount Orientation	Vertical
Number of Positions	24, 83
Board-to-Board Configuration	Parallel

Electrical Characteristics

Dielectric Withstanding Voltage (Max)	750 VAC
Insulation Resistance	1000 MΩ
Impedance	100 Ω



Operating Voltage	250 VAC
Signal Characteristics	
Data Rate	16 Gb/s
Body Features	
Primary Product Color	Black
Contact Features	
PCB Contact Termination Area Plating Material Thickness	.5 – 2.54 µm[19.685 – 100 µin]
Contact Layout	Staggered
Mating Tab Width	.69 mm, 4.5 mm[.027 in][.177 in]
Mating Tab Thickness	.41 mm[.015 in]
PCB Contact Termination Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.076 µm[3 µin]
Contact Type	Socket
Contact Current Rating (Max)	1.5 A
Termination Features	
Rectangular Termination Post & Tail Thickness	.15 mm[.005 in]
Rectangular Termination Post & Tail Width	.43 mm[.016 in]
Termination Post & Tail Length	1.47 mm[.057 in]
Termination Method to PCB	Through Hole - Press-Fit
Mechanical Attachment	
PCB Mount Alignment Type	Post Polarization
Mating Retention	With
Mating Alignment	With
PCB Mount Retention	With
PCB Mount Alignment	With
Connector Mounting Type	Board Mount
Housing Features	
Mating Entry Location	Top
Centerline (Pitch)	3.04 mm, 6.09 mm[.12 in][.24 in]



Housing Material	LCP (High Temp Thermoplastic)
------------------	-------------------------------

Dimensions

Connector Height	4.49 mm[.176 in]
PCB Thickness (Recommended)	.06 mm[.8 in]

Usage Conditions

Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Method	Box, Tray
------------------	-----------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>




Compatible Parts

 TE Part # 7-2143410-5 STRADA MESA,HD,HF,024,000,00,SN,N,25	 TE Part # 6-2143410-6 STRADA MESA,HD,HF,024,000,00,SN,N,16	 TE Part # 9-2143410-0 STRADA MESA,HD,HF,024,000,00,SN,N,40	 TE Part # 1-2143410-6 STRADA MESA,HD,HF,024,000,00,PB,N,16
 TE Part # 2-2143410-5 STRADA MESA,HD,HF,024,000,00,PB,N,25	 TE Part # 4-2143410-0 STRADA MESA,HD,HF,024,000,00,PB,N,40		

Customers Also Bought

 TE Part #1-2176058-4 RLP73M 3A R036 5% 2K RL	 TE Part #1892731-2 Assy 2x6 MINIPAK HDE seq2	 TE Part #5-104804-2 15 SYSTEM 50 HDR SRST SHRD SN	 TE Part #4-2176605-6 RLC73PD 3A R165 1% 2K RL
 TE Part #2204600-1 PDBB 125A POWER CONNECTOR, BOARD VERSION	 TE Part #2364123-1 80A BOARD MOUNT TRIBUTARY BUS BARS CONN	 TE Part #2-2344064-4 CONNECTOR ASSEMBLY, SMT, OSFP 112	 TE Part #2057989-1 IMP100S,R,RA6P14C,LG,39



Documents

Product Drawings

STRADA MESA,RC,HF,024,000,00,SN,N,NA

English

CAD Files

Customer View Model

ENG_CVM_CVM_5-2143411-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-2143411-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-2143411-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English