

This document was generated on 11/27/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 1203410506

Status: Active

Overview: Brad Industrial Ethernet Solutions

Description: Micro-Change M12 to Standard RJ-45 CAT6A Double-Ended Cordset, 8 Poles, Male

(Straight) to Male (Straight), 26 AWG, Shielded PUR Cable, 10.0m (32.81') Length

Documents:

<u>Drawing (PDF)</u> <u>Packaging Specification PK-120341-140 (PDF)</u>

Product Specification PS-120341-140-001 (PDF)

RoHS Certificate of Compliance (PDF)

General

Product Family Industrial Cordsets

Series 120108

Connector End A Micro-Change (M12)
Connector End B RJ-45 (standard)
IP Rating IP20, IP67
Material - Contact Brass

Overview Brad Industrial Ethernet Solutions

Performance Category 6/

Product Name Micro-Change (M12) Cat6A

Protocol N/A

Region America, Asia, Europe

Type Double Ended UPC 887191128108

Physical

Cable Diameter 6.40mm (.252")
Cable Length 10.0m (32.81')

Color - Cable Jacket
Coupling Style
Threaded
Gender
Male-Male
Keyway
X-coded
LED Indicator
No
Material - Cable Jacket
Material - Connector Body
Blue
Threaded
Male-Male
Male-Male
PUR

Material - Coupling Nut

Material - Plating Mating

Nickel-plated Brass

Gold over Nickel

Net Weight

461.000/g

Orientation Straight to Straight

Poles 8

Temperature Range - Operating -40°C to +70°C

Wire Size AWG 26

Wire/Cable Type Shielded PUR

Electrical


Current - Maximum per Contact 0.5A Voltage - Maximum 48V

Material Info

Engineering Number E26E06020M100

Reference - Drawing Numbers

Packaging Specification PK-120341-140
Product Specification PS-120341-140-001



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant with Exemption 6(c) REACH SVHC Not Contained Per -ED/01/2018 (15 January 2018) Halogen-Free Status

Not Low-Halogen

For more information, please visit Contact US

China ROHS 50 Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series

120108 Series

This document was generated on 11/27/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION