

## Han 10HP Direct/M-HTE-M32



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 39 710 0447                                                                        |
| Specification      | Han 10HP Direct/M-HTE-M32                                                             |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19397100447">https://b2b.harting.com/19397100447</a> |

### Identification

|                          |                              |
|--------------------------|------------------------------|
| Category                 | Hoods/Housings               |
| Series of hoods/housings | Han <sup>®</sup> HP Direct M |
| Type of hood/housing     | Hood                         |

### Version

|              |               |
|--------------|---------------|
| Locking type | Screw locking |
| Size         | 10 B          |
| Version      | Top entry     |
| Cable entry  | 1x M32        |

### Technical characteristics

|                                        |                                |
|----------------------------------------|--------------------------------|
| Tightening torque (screw locking)      | 4 Nm                           |
| Limiting temperature                   | -40 ... +125 °C                |
| Degree of protection acc. to IEC 60529 | IP66                           |
|                                        | IP68                           |
|                                        | IP69 / IPX9K acc. to ISO 20653 |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast   |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 9005 (jet black) |
| Material (seal)         | FPM                  |
| Material (locking)      | Stainless steel      |
| RoHS                    | compliant            |



Pushing Performance

## Material properties

|                             |           |
|-----------------------------|-----------|
| ELV status                  | compliant |
| China RoHS                  | e         |
| REACH Annex XVII substances | No        |
| REACH ANNEX XIV substances  | No        |
| REACH SVHC substances       | No        |

## Specifications and approvals

|                |                         |
|----------------|-------------------------|
| Specifications | EN 60664-1<br>IEC 61984 |
| CE             | Yes                     |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 277 g                                    |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |