



Part Number: 8778MN

SpaceMaker™, (6 pr) 22 AWG (19x34) TC, PP/PVC, Foil Shld

Product Description

Six 22 AWG pair stranded (19x34) TC conductors, polypropylene insulation, individual and overall Beldfoil® shield (100% coverage), PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
22	19x34	TC - Tinned Copper	12
Total Number of Pairs:			

Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.010 in

Color Chart

Number	Color
1	Black & White
2	Red & Dark Green
3	Brown & Dark Blue
4	Orange & Yellow
5	Purple & Gray
6	Pink & Tan

Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Tape	Aluminum Foil-Polyester Tape	Beldfoil	100 %	TC - Tinned Copper	24

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Таре	Aluminum Foil-Polyester Tape	Beldfoil	100 %	TC - Tinned Copper	22

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.317 in	0.016 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR 14.9 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor Nom. Capacitance Conductor to Shield

Inductance

Nominal Inductance

Voltage

UL Voltage Rating

Temperature Range

UL Temp Rating:	80°C
Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	61 lbs/1000ft
Max Recommended Pulling Tension:	157 lbs
Min Bend Radius During Installation:	1.270 in
Min Bend Radius (Continuous Flexing):	3.170 in

Standards

UL AWM Style:	AWM 2937 (300V 80C), NFPA 79	

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes

Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT2	
---------------------	-----	--

Part Number

Plenum (Y/N):	No
---------------	----

Variants

Item #	Color
8778MN 006100	BLUE, LIGHT
8778MN 0061000	BLUE, LIGHT
8778MN 008100	GRAY
8778MN 0081000	GRAY
8778MN 004100	YELLOW
8778MN 0041000	YELLOW

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be incompliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for

determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be incompliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.