



**Part Number: 37508**

Hook-Up/Lead Wire UL AWM Style 3499, (1) 8 AWG (84x27) TC, EPDM, 7500V, 150°C

**Product Description**

One 8 AWG stranded (84x27) tinned copper conductors, EPDM insulation.

**Technical Specifications**

Physical Characteristics (Overall)

**Conductor**

AWG	Stranding	Material	No. of Conductors
8	84x27	TC - Tinned Copper	1

Conductor Count:	1
------------------	---

**Insulation**

Material	Nominal Diameter	Nominal Wall Thickness
EPDM - Ethylene Propylene Diene Monomer Rubber	0.423 in	0.131 in
EPDM		

**Outer Jacket Material**

Nominal Diameter
0.423 in

Electrical Characteristics

**Conductor DCR**

Nominal Conductor DCR
0.6 Ohm/1000ft

**Current**

Max. Recommended Current [A]
Single conductor in free air @ 30C ambient 155 amps

**Voltage**

UL Voltage Rating
7500 VRMS UL AWM 3499

Temperature Range

UL Temp Rating:	150°C
-----------------	-------

Mechanical Characteristics

Bulk Cable Weight:	120.9 lbs/1000ft
--------------------	------------------

Standards

UL AWM Style:	3499
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Part Number

Plenum (Y/N):	No
---------------	----

Variants

Item #	Color
37508 0101000	BLACK
37508 01050	BLACK
37508 010500	BLACK

Product Notes

Notes:	Separator Material over Conductor: Y
--------	--------------------------------------

© 2018 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.