

**Part Number: 9932**



**RS232/423 Low Cap, #24-7c, FPO, O/A Foil+Braid, PVC Jkt, CM**

## Product Description

Computer EIA RS-232/423 Cable, 24 AWG stranded (7x32) tinned copper conductors, Datalene® insulation, overall Beldfoil® (100% coverage) + tinned copper braid shield (65% coverage), drain wire, PVC jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

| AWG | Stranding | Material           | No. of Conductors |
|-----|-----------|--------------------|-------------------|
| 24  | 7x32      | TC - Tinned Copper | 7                 |

|                  |   |
|------------------|---|
| Conductor Count: | 7 |
|------------------|---|

#### Insulation

| Material                  | Material Trade Name | Nominal Wall Thickness |
|---------------------------|---------------------|------------------------|
| FPE - Foamed Polyethylene | Datalene®           | 0.015 in               |

#### Color Chart

| Color  |
|--------|
| Black  |
| White  |
| Red    |
| Green  |
| Brown  |
| Blue   |
| Orange |

#### Outer Shield Material

| Type  | Layer | Material                     | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|-------|-------|------------------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Tape  | 1     | Aluminum Foil-Polyester Tape | Beldfoil®           | 100 %        | TC - Tinned Copper | 24            | Stranded mm                  |
| Braid | 2     | TC - Tinned Copper           |                     | 65 %         |                    |               |                              |

#### Outer Jacket Material

| Material                 | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.265 in         | 0.035 in               |

### Electrical Characteristics

#### Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 24 Ohm/1000ft         | 4.4 Ohm/1000ft           |

#### Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|-----------------------------------------|---------------------------------------------------------|
| 12 pF/ft                                | 22 pF/ft                                                |

#### Delay

| Max. Delay Skew | Nominal Velocity of Propagation (VP) [%] |
|-----------------|------------------------------------------|
| 78 ns/100m      | 78 %                                     |

Current

| Max. Recommended Current [A]    |
|---------------------------------|
| 1.5 Amps per conductor @ 25°C A |

Voltage

| UL Description    | UL Voltage Rating           |
|-------------------|-----------------------------|
| UL AWM Style 2919 | 30V RMS (UL AWM Style 2919) |
| CM                | 300 V RMS (CM)              |

Temperature Range

|                       |                          |
|-----------------------|--------------------------|
| UL Temp Rating:       | 80°C (UL AWM Style 2919) |
| Operating Temp Range: | -30°C To +80°C           |

Mechanical Characteristics

|                             |               |
|-----------------------------|---------------|
| Bulk Cable Weight:          | 37 lbs/1000ft |
| Min Bend Radius/Minor Axis: | 2.75 in       |

Standards

|                          |                  |
|--------------------------|------------------|
| NEC/(UL) Specification:  | CM               |
| CEC/C(UL) Specification: | CM               |
| UL AWM Style:            | 2919 (30 V 80°C) |
| CPR Euroclass:           | Eca              |

Applicable Environmental and Other Programs

|                                       |                               |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01                    |
| CA Prop 65 (CJ for Wire & Cable):     | Yes                           |
| MII Order #39 (China RoHS):           | Yes                           |

Flammability, LS0H, Toxicity Testing

|                  |                   |
|------------------|-------------------|
| UL Flammability: | UL1685 UL Loading |
|------------------|-------------------|

Part Number

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Variants

| Item #       | Color  |
|--------------|--------|
| 9932 060100  | CHROME |
| 9932 0601000 | CHROME |
| 9932 060500  | CHROME |

Product Notes

|        |                                                                                                                                                                                                                |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes: | Datalene® insulation features include a low dielectric constant and a low dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight. |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.