




备注：侧弹分为外弹与内弹

目錄 MAPX	设变内容 MODIFICATION	日期 DATE

NOTES:
Housing: Thermoplastics,UL94V-0
Contact: Copper Alloy
Shell: Copper Alloy/Steel
Voltage Current Rating:1.5 AMP. 30V AC
Insulation Resistance:1000MΩ Min.
Contact Resistance:30 MΩ Max.
Dielectric Withstanding Voltage:500W AC
Temperature Range:-35℃ to +85℃
Insulator color: Black/White
Plastic material:PBT/LCP/Others
Shell finish:Nickel plated/Tin-Lead plated
Mechanical:
Mating Force:3.5KG MAX
Unmating Force:0.7 KG MIN.
Contact finish:
01:Selective Gold Flash
02:Selective Gold 3U"
03:Selective Gold 5U"
04:Selective Gold 15U"
05:Selective Gold 30U"

产品图 PRODUCT CHART DWG		深圳市精拓金电子有限公司					
公差一览表 TOLERANCE UNLESS OTHERWISE		单位 UNITS	MM	制图 DRAWING	Z-Y-B	产品料号 PRODUCT PART NO.	903-232A2021S10100
X.	±0.15	X'.	±5'	比例 SCALE	1:1	审核 CHKD	雷永键
.XX	±0.10	.XX'	±2'	日期 DATE	2009/10/20	核准 APPD	雷永键
.XXX	±0.05	.XXX'	±1'	角法 VIEW		版本 VER	A0
.XXX	±0.03	.XXX'	±0.5'				