

PRODUCTS

Rocker switches

Pushbutton switches

Toggle switches

Slide switches

Rotary switches

Foot switches

Tact and key switches

Snap-action switches

Micro-signal switches

ECO switches

Sensors

Systems and modules

Accessories

General information

Catalog request /
download

PRODUCTS ▶ PUSHBUTTON SWITCHES

Pushbutton switches

SERIES 5000 - ROUND PUSHBUTTON SWITCHES - FOR AT LEAST 200 000 MECHANICAL SWITCHING CYCLES

◀ Show previous product

Show next product ▶

5000.0211

Drawing

Similar to original
product

→ Print data sheet

Product number	5000.0211
Actuator color / printing	
Miscellaneous	fixing pin
Switching function	Normally open contact (SPNO)
Number of poles	1-pole
connections	Quick-connect terminal, 2.8
Mechanical life endurance	20E4
Rating IEC	4 (2) A 250 V AC 5E4
Rating North America	2 A 250 V AC 1/10 HP 4 A 125 V AC 1/10 HP
Proof tracking	250 PTI
Protection type	Connection IP 40
Ambient temperature	-20 °C ... +85 °C
Ambient temperature	-20 °C ... +55 °C
Flammability	UL 94 V-2
Glow wire test temperature	850 °C
Actuators and additional actuators	PA glass fiber-reinforced, gray
Housing description	PA glass fiber-reinforced, black
Connection surface	external connection silver plated
Contact material	Ag
Contact distance	≥ 3 mm
Plug force of the terminals	≤ 64 N
Pretravel max.	2.0 ±0.4 mm
Total travel / stroke	4.0 mm
Approval marks	CSA / UL / ENEC 05
Suitable for appliances of protection class	I
Type of fastening	Snap fastening
Shop / Stock version	