




Connectors > Contacts > Connector Contacts > DYNAMIC 3000 CONTACT



Contact Type: **Receptacle**
Contact Mating Area Plating Material: **Tin**
Wire Size: **1.23 – 2.27 mm²**
Product Terminates To: **Wire & Cable**

[All DYNAMIC 3000 CONTACT \(91\)](#)

Features

Contact Features

Mating Tab Width	2 mm[.08 in]
Mating Tab Thickness	.64 mm[.025 in]
Contact Type	Receptacle
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	15 A

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Dimensions

Wire Size	1.23 – 2.27 mm²
-----------	-----------------

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------



Packaging Features

Packaging Method	Bag & Box
------------------	-----------

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # CAT-D9934-A75C DYNAMIC 3500 REC AND TAB HSG	 TE Part # 91561-1 CCII D-3 3L REC TAB 16-14 ASSY	 TE Part # 234168-1 EXTRACTION TOOL(DYNAMIC D-3)	 TE Part # 917249-1 DYNAMIC D-3400F REC HSG 20P
--	---	--	---



TE Part # 178214-1
DYNAMIC 3400 REC HSG 12P



TE Part # 1-917266-3
DYNAMIC D-3200 P/MOUNT REC HSG




TE Part # 2255149-1
MINI SAHT D3000-3L

Also in the Series | Dynamic 3000 Series




Connector Contacts(94)




Connector Hardware(8)



Insertion & Extraction Tools(2)



PCB Headers & Receptacles(283)



PCB Terminal Blocks(37)



Standard Rectangular Connectors(2)



Wire-to-Board Connector Assemblies & Housings(152)

Customers Also Bought



TE Part #1903126-1
Contact: Component To Wire; 3-5A, 30-18 Wire Size




TE Part #170887-3
IS SHUR PLG 5 DIA NAT



TE Part #170092-4
FF 250 REC 18-14AWG TPBR REREELING



TE Part #500031-1
SPIRAP 1/2" PE, OUTDR,BLK,50FT




TE Part #170286-1
MIC REC CONTACT



TE Part #C58LL-RPSM-2438-NM
RP-SMA to N Type 2458mm RG58



TE Part #YS8966
YAGI,SS,6,896-970MHz, 16,9dBi



TE Part #172203-1
ECONOSEAL-J CONN RUBBER 3P



Documents

Product Drawings

DYNAMIC D-3 REC CONT. 3L PRE-TIN L/P

English

CAD Files

Customer View Model

ENG_CVM_1-353717-5_B.3d_igs.zip

English

Customer View Model

ENG_CVM_1-353717-5_B.3d_stp.zip

English

Customer View Model

ENG_CVM_1-353717-5_B.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

English

Instruction Sheet (non U.S.)

Japanese

Agency Approvals

TUV Certificate

English

TUV Certificate

English