



+ RELAYS, CONTACTORS & SWITCHES
PROTECTIVE RELAYS



✓ Active

TE CONNECTIVITY (TE)
WOV-3-220=WILMAR OVERVOLTAGE R
CII | WUV

WOV-3-220
TE Internal Number: 1-1618108-9

Not EU RoHS Compliant
Not EU ELV Compliant
Contact Arrangement 1 Form A, SPST-NO, 1 NO
Contact Current Rating (A) 5
Input Voltage (VAC) 220
Time Delay Without
Phase Three

DOCUMENTATION

No documentation available.

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Protection Function Overvoltage
Time Delay Without
Phase Three
Product Type Relay
Relay Type Protective Relay

Electrical Characteristics

Input Voltage (VAC) 220
Actuating System AC

Signal Characteristics

Frequency Adjustment (Hz) 50 – 400

Contact Features

- Type of Control Potentiometer Adjustable
- Contact Arrangement 1 Form A, SPST-NO, 1 NO
- Contact Current Rating (A) 5
- Contact Arrangement (Additional Output) 1 Form B, SPST-NC, 1 N/C

Dimensions

Dimensions (L x W x H) (Approximate) 88.9 x 98.29 x 76.2 mm [3.5 x 3.87 x 3 in]

Usage Conditions

Operating Temperature Range (°C) -20 – 65

Operation/Application

Mode of Operation Adjustable Pick-Up

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance
PDF