




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **5.21 mm [ .205 in ]**

Mating Tab Thickness: **.81 mm [ .032 in ]**

Features

Product Type Features

|                 |        |
|-----------------|--------|
| Insertion Force | Normal |
|-----------------|--------|

Configuration Features

|                                   |               |
|-----------------------------------|---------------|
| Connection Capacity               | Single        |
| Compatible With Wire & Cable Type | Discrete Wire |

Contact Features

|                                |                  |
|--------------------------------|------------------|
| Quick Disconnect Terminal Type | Receptacle       |
| Mating Tab Width               | 5.21 mm[.205 in] |
| Mating Tab Thickness           | .81 mm[.032 in]  |
| Terminal Orientation           | Straight         |
| Contact Base Material          | Brass            |
| Terminal Plating Material      | Unplated         |
| Crimp Type                     | F-Crimp          |
| Barrel Type                    | Open             |

Termination Features

|  |  |
|--|--|
|  |  |
|--|--|



|                       |              |
|-----------------------|--------------|
| Product Terminates To | Wire & Cable |
|-----------------------|--------------|

Mechanical Attachment

|                         |                    |
|-------------------------|--------------------|
| Extraction Force        | 19.6 – 68.6 Newton |
| Wire Insulation Support | With               |
| Mating Retention Type   | Dimple             |

Dimensions

|                                      |                             |
|--------------------------------------|-----------------------------|
| Terminal Material Thickness          | .41 mm[.016 in]             |
| Product Length                       | 17.5 mm[.688 in]            |
| Compatible Insulation Diameter Range | 3.3 – 4.6 mm[.13 – .181 in] |
| Wire Size                            | .82 – 2.08 mm²              |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Insulation Option           | Uninsulated                |
| Operating Temperature Range | -40 – 110 °C[-40 – 230 °F] |

Industry Standards

|                                           |         |
|-------------------------------------------|---------|
| Compatible With Agency/Standards Products | CSA, UL |
|-------------------------------------------|---------|

Packaging Features

|                    |            |
|--------------------|------------|
| Packaging Quantity | 7000       |
| Packaging Method   | Strip/Reel |

Other

|      |         |
|------|---------|
| Line | Premier |
|------|---------|

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                             |



Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 170181-4  
205 FASTON,REC.,22-18 AWG,BR

TE Part # 2150084-1  
OCEAN\_2.0\_APPLICATOR-E-100F180F-REM

TE Part # 2150084-2  
OCEAN\_2.0\_APPLICATOR-E-100F180F-REA

TE Part # 42239-4  
205 FASTON REC 18-14 AWG PHBZ

TE Part # 7-2150084-7  
OCEAN\_2.0\_SPARE\_PART\_KIT-100F180F

TE Part # 409774-1  
DAHT FASTON 18-14 ASSY

Also in the Series | FASTON 205

Crimp Terminal Housings(3)

PCB Terminals(10)

Quick Disconnects(35)

Customers Also Bought





TE Part #7-1623795-4  
SQP10 150R 10% Wire

TE Part #4-1419111-1  
PT270012

TE Part #5557484-1  
MJ,TE,8P,SHLD,LOW PNL STR

TE Part #60850-1  
187 FASTON TAB 18-14 AWG BR

TE Part #5-1415043-1  
PT78602

TE Part #7-534998-6  
52 MODIV VRT DR CE 100/125

TE Part #5-1879352-9  
RR02 5% 82R AMMO

TE Part #6-1879352-0  
RR02 5% 91R AMMO

TE Part #1393310-3  
VCF4-1000=FROM SEC

Documents

Product Drawings

205 FASTON,REC.,18-14 AWG,BR

English

CAD Files

Customer View Model

ENG\_CVM\_CVM\_170179-1\_F.2d\_dxf.zip

English

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_170179-1\_F.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_170179-1\_F.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications



Application Specification

English

Agency Approvals

UL Report

English