
## Thermofit Molded Parts Specification Control Drawing Limited Distribution

Part Number : 234A011 thru 052-XXS

Boot, Rectangular, D-Subminiature, 90°, Side Entry, with Heat Recoverable Screen Description :

1. All dimensions are in  $\frac{\text{Incres}}{[\text{millimeters}]}$ 

- 2. Dimensions appearing in table are as follows:
  - a As Supplied
  - b After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added entry diameters will be reduced by .06 max.
  - a- Conductive thermoplastic adhesive
  - b- Structural thermoplastic adhesive






TABLE OF DIMENSIONS													
PART	Н		J		к		Р	R	s		U	w	×
NUMBER	Min	Max	Min	Max	Min	Max	Ref	Ref	Ref	Min	±20%	±20%	±20%
	a	b	a	b	a	b	ь	b	b	a	b	b	b
234A011-XXS	.82	.80	<u>.62</u>	. <u>42</u>	.35	<u>16</u>	1.02	. <u>87</u>	<u>.59</u>	.12	. <u>18</u>	.04	.12
	[20,8]	[20,3]	[15,7]	[10,7]	[9,0]	[4,1]	[26,0]	[22,0]	[15,0]	[3,0]	[4,6]	[1,0]	[3,0]
234A021-XXS	1.14	1.11	.62	. <u>42</u>	.43	.21	1.22	. <u>98</u>	<u>.75</u>	.15	.26	.04	.12
	[29,0]	[28,2]	[15,7]	[10,7]	[11,0]	[5,3]	[31,0]	[25,0]	[19,0]	[3,8]	[6,5]	[1,0]	[3,0]
234A032-XXS	1.69	1.66	.62	.42	.59	.32	1.69	1 <u>.10</u>	. <u>87</u>	.20	.30	.04	.12
	[42,8]	[42,2]	[15,7]	[10,7]	[15,0]	[8,1]	[43,0]	[28,0]	[22,0]	[5,0]	[7,5]	[1,0]	[3,0]
234A036-XXS	2.40	2.17	.55	. <u>42</u>	.78	.41	2.08	1 <u>.53</u>	1 <u>.30</u>	.20	. <u>39</u>	.04	.12
	[61,0]	[55,1]	[14,0]	[10,7]	[20,0]	[10,6]	[53,0]	[39,0]	[33,0]	[5,0]	[10,0]	[1,0]	[3,0]
234A042-XXS	2.34	2.31	.59	<u>.42</u>	.75	.34	2.09	1 <u>.18</u>	<u>.98</u>	.24	<u>.39</u>	.04	.12
	[59,5]	[58,7]	[15,0]	[10,7]	[19,0]	[8,6]	[53,0]	[30,0]	[25,0]	[6,0]	[10,0]	[1,0]	[3,0]
234A052-XXS	2.26	2.28	<u>.65</u>	<u>.54</u>	.75	. <u>42</u>	2.20	1 <u>.26</u>	<u>.98</u>	.24	<u>.39</u>	.04	.12
	[57,5]	[57,9]	[16,5]	[13,7]	[19,0]	[10,7]	[56,0]	[32,0]	[25,0]	[6,0]	[10,0]	[1,0]	[3,0]

Raychem

Revision : E

Part Number :

234A011 thru 052-XXS

Date: 5/5/99 Description :


Boot, Rectangular, D-Subminiature, 90°, Side Entry, with Heat Recoverable Screen

## Thermofit Molded Parts Specification Control Drawing Limited Distribution

234A011 THRU 052-XXS Part Number :

Boot, Rectangular, D-Subminiature, 90°, Side Entry, with Heat Recoverable Screen Description :

COMPATABILITY CHART									
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION				
-3\$	Polyolefin/Copper Composite	RT-1370	/200	N/A	Adhesives				
-25S	Elastomer/Copper Composite	RT-1371	/200	N/A	Adhesives				



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision : E Date: 5/5/99 Part Number : 234A011 thru 052-XXS

Boot, Rectangular, D—Subminiature, 90°, Side Entry, with Heat Recoverable Screen Description :

CAD FILE MP99092