1-368575-6 V ACTIVE

Power Double Lock

TE Internal #: 1-368575-6

Housing, Plug, Wire-to-Board / Wire-to-Wire, 4 Position, 3.96 mm [. 156 in] Centerline, Wire & Cable, Power Double Lock, Rectangular

Power Connectors

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > Glow Wire Power Double Lock Plug











Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug

Connector System: Wire-to-Board, Wire-to-Wire

Number of Positions: 4

Centerline (Pitch): 3.96 mm [.156 in]

All Glow Wire Power Double Lock Plug (55)

Features

Product Type Features

Compatible With Discrete Wire Type	Stranded
Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Board, Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	4
Number of Power Positions	0
Number of Signal Positions	0

2

Electrical Characteristics

Number of Rows



Operating Voltage	300 VAC
Contact Features	
Contact Layout	Matrix
Contact Retention Within Housing	Without
Contact Type	Receptacle
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Blue
Housing Material	PA 66
Dimensions	
Row-to-Row Spacing	4.6 mm[.181 in]
Usage Conditions	
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Compatible With Agency/Standards Products	USR
Compatible With Approved Standards Products	UL 1977
UL Flammability Rating	UL 94V-0
Glow Wire Rating	GWT 750°C (Without Flame)
Packaging Features	
Packaging Quantity	300
Packaging Method	Bag
Product Compliance For compliance documentation, visit the product page on TE.com>	

Compliant

EU RoHS Directive 2011/65/EU



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts











Also in the Series | Power Double Lock





Connector Contacts(24)



Connector Hardware(14)



Insertion & Extraction Tools(2)



PCB Headers & Receptacles(43)



Customers Also Bought



TE Part #177915-1

AMP POWER DBL LOCK REC (L)



TE Part #177917-1

AMP POWER DBL LOCK TAB (L)



TE Part #2005247-2 Glow Wire Power Double Lock Plug



TE Part #2005249-1
PDL 2P CAP 3.96 P/M(GWT) NAT







Documents

Product Drawings

PDL 4P PLUG 3.96 D/R(GWT) BLU

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_1-368575-6_B.2d_dxf.zip

Housing, Plug, Wire-to-Board / Wire-to-Wire, 4 Position, 3.96 mm [.156 in] Centerline, Wire & Cable, Power Double Lock, Rectangular Power Connectors



English

Customer View Model

ENG_CVM_CVM_1-368575-6_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-368575-6_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English