

# DATASHEET


## C0805C0G500-150KNP

GENERAL PURPOSE CERAMIC CAPACITORS (C SERIES)

0805, C0G, 50V, 15pF,  $\pm 10\%$ , 100% matte Tin(Sn) over Nickel



VENKEL LTD.



### SIZE SPECIFICATIONS units: inches

|            |               |
|------------|---------------|
| Length:    | 0.080         |
| Width:     | 0.050         |
| T(max):    | 0.055         |
| Min E/B:   | .02 $\pm$ .01 |
| Size(EIA): | 0805          |

### COMPONENT SPECIFICATIONS

|                    |                                |
|--------------------|--------------------------------|
| Category:          | Ceramic Capacitors             |
| Series:            | General Purpose (C Series)     |
| Size:              | 0805                           |
| Dielectric:        | C0G                            |
| Voltage:           | 50V                            |
| Capacitance:       | 15pF                           |
| Tolerance:         | $\pm 10\%$                     |
| Termination:       | 100% matte Tin(Sn) over Nickel |
| Packaging:         | Paper Tape (7" Reel)           |
| Quantity per Reel: | 4,000                          |

### DIELECTRIC SPECIFICATIONS

|                                 |                                       |
|---------------------------------|---------------------------------------|
| Temperature Coefficient:        | 0 $\pm 30$ PPM/ $^{\circ}$ C          |
| Temperature Voltage Coefficient | 0 $\pm 30$ PPM/ $^{\circ}$ C          |
| Ageing:                         | None                                  |
| Withstanding Voltage:           | >2.5 times VDCW                       |
| Operating Temp:                 | -55 $^{\circ}$ C to +125 $^{\circ}$ C |
| Dissipation Factor:             | 0.1% max                              |

### COMPLIANCE STATUS

|                         |                       |
|-------------------------|-----------------------|
| RoHS Status             | 6 of 6 Compliant      |
| REACH Status            | Compliant             |
| Halogen Status          | Halogen Free          |
| Conflict Mineral Status | Conflict Mineral Free |

### REEL DIMENSIONS units: mm

| Tape | B min | C            | A(7")         | A(13")        | D Min | N Min | G            | T max |
|------|-------|--------------|---------------|---------------|-------|-------|--------------|-------|
| 8mm  | 0.30  | 13 $\pm$ .05 | 178 $\pm$ 2.0 | 330 $\pm$ 2.0 | 20.20 | 50.00 | 10 $\pm$ 1.5 | 14.90 |

### TAPING SPECIFICATIONS units: mm

| A                    | B             | W             | F             | E              | Po            |
|----------------------|---------------|---------------|---------------|----------------|---------------|
| 1.16 $\pm$ 0.2       | 2.4 $\pm$ 0.2 | 8.0 $\pm$ 0.2 | 3.5 $\pm$ 0.1 | 1.75 $\pm$ 0.1 | 4.0 $\pm$ 0.1 |
| Pz                   | D             | T             | P             | To             | T(E)          |
| 2.0 $\pm$ 0.05 - 0.0 | 1.5 $\pm$ 0.1 | 1.15 MAX      | 4.0 $\pm$ 0.1 |                |               |