

MQS

TE Internal #: 953382-2


Cover - Cable Exit, Cable Exit Angle 180°, White, PBT GF, -40 – 100

°C [-40 – 212 °F], Automotive Connector Caps & Covers

View on TE.com >



Connectors > Automotive Connectors > Automotive Connector Accessories > Automotive Connector Caps & Covers



Protection & Strain Relief Accessory Type: Cover - Cable Exit

Cable Exit Angle: 180°
Strain Relief: Without

Primary Product Color: White

Primary Product Material: PBT GF

Features

Product Type Features

Product Type Features	
Protection & Strain Relief Accessory Type	Cover - Cable Exit
Body Features	
Cable Exit Angle	180°
Primary Product Color	White
Primary Product Material	PBT GF
Mechanical Attachment	
Strain Relief	Without
Dimensions	
Compatible Cable Bundle Diameter Range	5 mm[.197 in]
Usage Conditions	
Operating Temperature (Max)	100 °C[212 °F]
Operating Temperature Range	-40 - 100 °C[-40 - 212 °F]
Industry Standards	
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Method	Box
Other	

Yes

Serviceable



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought






TE Part #185311-1 6POS MQS REC



TE Part #953382-1 COVER FOR 6W HSG MQS GEN2




TE Part #953381-1 LOCKING DEVICE FOR 6W MQS



TE Part #1123371-1 040-3 MLC PLUG HSG ASSY 16P



TE Part #316836-1 040-3 REC CONT. S



TE Part #5-928999-5 MQS0,63 Au rec LL unseal. >0,2-0,35



TE Part #CT02193001 CL105-4X2X0.75-PO-0CK5500





TE Part #2334175-1
RESOLVER,STATOR SCR405 VSEA
TESTED HIGH



Documents

Product Drawings

COVER FOR 6W HSG MQS GEN2

English

CAD Files

Customer View Model

ENG_CVM_953382-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_953382-2_A.3d_stp.zip

English

Customer View Model

ENG_CVM_953382-2_A.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Cover - Cable Exit, Cable Exit Angle 180°, White, PBT GF, -40 – 100 °C [-40 – 212 °F], Automotive Connector Caps & Covers



Product Specification

English

Instruction Sheets

6 VOIES MQS GENE II

English

Instruction Sheet (non U.S.)

English