


**Trunnion support**  
**LNZG-40/50**  
Part number: 32960



 [General operating condition](#)

**Data sheet**

| Feature                                            | Value                                                                                                                                                                                                                             |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                               | 40/50                                                                                                                                                                                                                             |
| Based on norm                                      | ISO 15552                                                                                                                                                                                                                         |
| Corrosion resistance class (CRC)                   | 2 - Moderate corrosion stress                                                                                                                                                                                                     |
| LABS (PWIS) conformity                             | VDMA24364-B2-L                                                                                                                                                                                                                    |
| Suitability for the production of Li-ion batteries | Metals with more than 1% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils |
| Ambient temperature                                | -40 °C ... 80 °C                                                                                                                                                                                                                  |
| Product weight                                     | 129 g                                                                                                                                                                                                                             |
| Note on materials                                  | RoHS-compliant                                                                                                                                                                                                                    |
| Mounting material                                  | Wrought aluminum alloy                                                                                                                                                                                                            |
| Material of bearing                                | Polymer                                                                                                                                                                                                                           |