



Connectors > Lighting Connectors > Plug & Socket Lighting Connectors



Connector System: **Wire-to-Wire**
Number of Positions: **4**
Centerline (Pitch): **.14 mm [3.5 in]**
Sealable: **Yes**
Connector & Contact Terminates To: **Wire & Cable**

Features

Product Type Features

Connector System	Wire-to-Wire
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Lighting Connector Style	Receptacle

Configuration Features

Number of Positions	4
---------------------	---

Electrical Characteristics

Operating Voltage	250 VDC
-------------------	---------

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Current Rating (Max)	5 A
------------------------------	-----

Housing Features

--	--



Centerline (Pitch)	.14 mm[3.5 in]
--------------------	----------------

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 2106124-2 Contact, Tab, Tin Plated, Std Lgth	 TE Part # 2-2106124-2 Contact, Tab, Tin Plated, 22-26 AWG	 TE Part # 2-2106124-7 Contact, Tab, Tin Plated, LP 22-16 AWG	 TE Part # 2106124-9 Contact, Tab, Tin Plated, Std Lgth, LP
---	--	---	---



TE Part # 2106135-4
Assembly, Free Hanging Plug, SLC, 4 pos

Also in the Series

SlimSeal Connectors Headers

Plug & Socket Lighting Connectors(33)

Customers Also Bought

TE Part #183040-1
CPC SQ.FL.RCPT STD SEX SIZE

TE Part #1SET411304R0000
WD-1-RT-4080

TE Part #2106124-2
Contact, Tab, Tin Plated, Std Lgth

TE Part #63009-2
250 FASTON FLAG REC 18-14 AWG TPBR

TE Part #1-2106123-1
CONTACT,Recept, SLC, Tin Plated, On Stri

TE Part #2-2106124-2
Contact, Tab, Tin Plated, 22-26 AWG

TE Part #1SNL316010R0000
DBL160

TE Part #2106135-4
Assembly, Free Hanging Plug, SLC, 4 pos

TE Part #2-2106124-3
CONTACT, SEALED LIGHTING CONN, 22-24 AWG



Documents

Product Drawings

Assembly, Receptacle, 4-Position

English

CAD Files

Customer View Model

ENG_CVM_CVM_2106136-4_A1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2106136-4_A1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_2106136-4_A1.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

SLIMSEAL_SSL_CONNECOTS

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English