



ALPHA 400, wall-mounted cabinet, Flush-mounting, IP31, type of protection 1, H: 1250 mm, W: 550 mm, T: 210 mm, RAL 9016

Model	
product brand name	ALPHA
product designation	Wall-mounted cabinet
design of the product	Flush mounting
surface processing	powder-coated
Protection class	
protection class IP	IP31
operating resource protection class	Safety class 1
IK protection class	IK09
suitability for interaction lightning protection	Yes
suitability for use for outside use	No
Appearance	
RAL color number	9016
product component	
• cable entry	Yes
• mounting plate	No
product extension optional side-by-side mounting	No
number of rows	16
Mechanical Design	
height	1 263 mm
width	562 mm
depth	210 mm
installation depth	210 mm
number of modular width units	192
number of modular width units per DIN mounting bar	12
fastening method	flush mounting
net weight	22 kg
material of the enclosure	Steel

Approvals Certificates
General Product Approval



[Confirmation](#)



[Miscellaneous](#)



Test Certificates	other	Environment
-------------------	-------	-------------

- [Type Test Certific-](#)
- [Special Test Certific-](#)
- [Miscellaneous](#)
- [Confirmation](#)
- [Environmental Con-](#)
- [Environmental Con-](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8GK1121-6KK22>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8GK1121-6KK22>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8GK1121-6KK22

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

7/7/2024

