




目錄 MAPX	設變內容 MODIFICATION	日期 DATE

- Note:
- Material:
 - Housing: High temperature thermoplastic with g.f,UL94v-0
 - Contact: copper alloy,t=0.20mm
 - Shell: copper alloy,t=0.25mm
 - Specification:
 - Current rating:1.5PIN 1.8A Max/2,3,4PIN 1A Max.
 - Dielectric withstanding voltage: 100 V(ac) for 1 min.
 - Contact resistance: 30 mΩ Max.
 - Insulation resistance: 100 MΩ Min.
 - Total mating force: 3.57 Kg Max.
 - Total unmating force: 1.0 Kg Min
 - Temperature range: -30°C~80°C

产品图 PRODUCT CHART DWG		深圳市精拓金电子有限公司							
公差一览表 TOLERANCE UNLESS OTHERWISE				单位 UNITS	MM	制图 DRAWING	尹先华	产品料号 PRODUCT PART NO.	920-D52A2021S10102
X.	±0.30	X'.	±5°	比例 SCALE	1:1	审核 CHKD	郭治富	产品名称 PRODUCT NO.	MICRO 5P B型两脚贴板有边无柱LCP黑胶短端SMT
.X	±0.25	.X*	±2°						
.XX	±0.15	.XX*	±1°	日期 DATE	2021-04-16	核准 APPD	黄国荣	角法 VIEW	
.XXX	±0.10	.XXX*	±0.5°						
								版本 VER	A0