

EM-CPS-405 - Power distribution board




1002635

<https://www.phoenixcontact.com/us/products/1002635>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Modular power distribution board with CrossLink® interface, 125 A, 3-pos., touch-proof and protection against polarity reversal, width: 405 mm



Your advantages

- Protection against polarity reversal - phase rotation not possible
- Quick, complete out-of-the-box system
- Compact design compared to conventional power distribution

Commercial data

Item number	1002635
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C470
Product key	CK7811
Catalog page	Page 52 (C-5-2019)
GTIN	4055626468204
Weight per piece (including packing)	1,410.3 g
Weight per piece (excluding packing)	1,367.3 g
Customs tariff number	85369095
Country of origin	DE

EM-CPS-405 - Power distribution board



1002635

<https://www.phoenixcontact.com/us/products/1002635>

Technical data

Notes

Assembly note	We recommend using the high DIN rail (35x15) for optimum stability and maximum load. For detailed technical information, please refer to the packing slip. Torque for screwing on the power distribution board: 1.5 Nm (13lb-in).
---------------	---

Product properties

Product type	Assembly adapter
Product family	CrossPowerSystem

Data management status

Article revision	00
------------------	----

Electrical properties

Rated voltage	600 V DC (IEC)
	690 V AC (IEC)
	600 V AC/DC (UL)
Rated peak withstand current	25 kA
Rated current	125 A (IEC)
	100 A (UL)
Rated insulation voltage	800 V AC
Rated surge voltage	6 kV

Dimensions

Width	405 mm
Height	160 mm
Depth	45.1 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
----------------------	------

Approvals

UL data

SCCR	10 kA (unprotected)
	100 kA (protected)
	100 kA (CB 125 A/480 V AC)
	65 kA (CB 125 A/600 V AC)
	100 A (Class J 175 A)

Standards and regulations

Standards/regulations	IEC 61439-2
-----------------------	-------------

EM-CPS-405 - Power distribution board



1002635

<https://www.phoenixcontact.com/us/products/1002635>

	GB/T 7251.1
--	-------------

EM-CPS-405 - Power distribution board



1002635

<https://www.phoenixcontact.com/us/products/1002635>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1002635>



EAC
Approval ID: RU C-DE.A*30.B.01742



EAC
Approval ID: RU*DE*08.B.01841/19



UL Listed
Approval ID: E123528



cUL Listed
Approval ID: E123528

cULus Listed

EM-CPS-405 - Power distribution board



1002635

<https://www.phoenixcontact.com/us/products/1002635>

Classifications

ECLASS

ECLASS-11.0	27371392
ECLASS-13.0	27371392
ECLASS-12.0	27371392

ETIM

ETIM 9.0	EC002498
----------	----------

UNSPSC

UNSPSC 21.0	39121100
-------------	----------

EM-CPS-405 - Power distribution board



1002635
<https://www.phoenixcontact.com/us/products/1002635>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com