



Connectors > PCB Connectors > PCB Headers & Receptacles



Connector System: **Wire-to-Board**

Number of Positions: **5**

Number of Rows: **1**

Centerline (Pitch): **3.96 mm [.156 in]**

PCB Mount Orientation: **Vertical**

Features

Product Type Features

Connector Shape	Rectangular
Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header

Configuration Features

Number of Power Positions	5
Number of Loaded Positions	3
Number of Positions	5
Number of Rows	1
PCB Mount Orientation	Vertical

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------



Body Features

Connector Profile	Low
Primary Product Color	Natural

Contact Features

Contact Mating Area Length	7.7 mm[.303 in]
Contact Size	1.14mm
PCB Contact Termination Area Plating Material Thickness	1 µm[39.37 µin]
Contact Layout	Inline
Contact Underplating Material Thickness	.8 – 1.8 µm[31.5 – 70.86 µin]
Contact Mating Area Plating Material Thickness	1 µm[39.37 µin]
Contact Shape & Form	Square
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Brass
Contact Mating Area Plating Material	Tin
Contact Type	Tab
Contact Current Rating (Max)	8 A

Termination Features

Square Termination Post & Tail Dimension	1.14 mm[.045 in]
Termination Post & Tail Length	3.7 mm[.146 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Alignment Type	Polarization
Mating Retention	With
Mating Retention Type	Locking Tab
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	Without

Housing Features

Housing Material	Nylon
Centerline (Pitch)	3.96 mm[.156 in]



Dimensions

Connector Length	19.74 mm[.777 in]
Connector Height	9.2 mm[.36 in]
Connector Width	8.5 mm[.334 in]
PCB Thickness (Recommended)	1.6 mm[.063 in]

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Glow Wire Rating	GWT 750°C (Without Flame)
UL Flammability Rating	UL 94V-2

Packaging Features

Packaging Quantity	1000
Packaging Method	Bag

Other

Position Locations Omitted	2, 4
Number of Blocked Positions	2

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1-1123723-5 3.96 EP HDR ASSY 5P(NATURAL)	 TE Part # 1-1123724-3 3.96EP HDR ASSY 3(5)P NATURAL	 TE Part # 1-1318301-3 3.96EP HDR ASSY 3(5)P NAT/TUBE	 TE Part # 7-1123724-5 3.96EP HDR ASSY 5(9)P NATURAL, GWT
 TE Part # 5-1123723-5 3.96 EP HDR ASSY 5P(BLACK)	 TE Part # 1744416-5 5 POS EP II HSG, GLOW WIRE	 TE Part # 4-1123723-5 3.96 EP HDR ASSY 5P(RED)	 TE Part # 7-1123724-6 7.92EP HDR ASSY 6(11)P NATURAL GWT
 TE Part # 4-1123724-3 3.96EP HDR ASSY 3(5)P RED	 TE Part # 1744495-5 05P EP-II HOUSING, GREEN	 TE Part # 3-1123723-5 3.96 EP HDR ASSY 5P(BLUE)	 TE Part # 7-1123724-1 3.96EP HDR ASSY 4(7)P (NATURAL GWT)
 TE Part # 7-1123724-2 03P EP HDR HSG V0 GWT NO 02P			



Also in the Series | Economy Power

Connector Contacts(15)	Connector Hardware(2)	Insertion & Extraction Tools(1)	PCB Headers & Receptacles(400)
Rectangular Connector Housings(1)	Rectangular Power Connectors(64)	Wire-to-Board Connector Assemblies & Housings(142)	

Customers Also Bought

 TE Part #2199119-4 M.2 0.5PITCH 3.2H KEY E 15U" AU	 TE Part #66104-9 III+ SKT,24-20,30AU/FL,STRIP	 TE Part #1825010-1 ASE2204=DPDT AUTOSLIDE	 TE Part #1473565-8 RITS CONN.HDR ASSY 8P
 TE Part #1-1734742-2 .5 FPC VT ZIF Type-A 12 CONT	 TE Part #641966-1 03P UMNL PIN HDR ASSY 94VO	 TE Part #60465-1 250 FASTON TAB BR	 TE Part #2-34161-1 TERMINAL,PG R 16-14 10
 TE Part #881545-2 SHUNT LP W/HANDLE 2 POS 30AU			



Documents

Product Drawings

3.96EP HDR ASSY 3(5)P (NATURAL GWT)

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_7-1123724-3_AD.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_7-1123724-3_AD.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_7-1123724-3_AD.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

1-1773885-9 Economy Power Connectors

English

Product Specifications

Application Specification

English

Agency Approvals

VDE Certificate

English