

1414003

https://www.phoenixcontact.com/pc/products/1414003

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Housing screw connection, Socket, M12, Rear mounting, M15 x 1, THR solder connection, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1239055

Your advantages

- · Easy device integration, thanks to mechanical port screw connections with threaded fastening
- · Flexible PCB assembly: two-piece connectors for wave and THR soldering

Commercial data

Item number	1414003
Packing unit	20 pc
Minimum order quantity	20 pc
Product key	ABQADE
GTIN	4055626022604
Weight per piece (including packing)	10.79 g
Weight per piece (excluding packing)	10.16 g
Customs tariff number	79070000
Country of origin	DE



1414003

https://www.phoenixcontact.com/pc/products/1414003

Technical data

Notes

Notes on operation	The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Order information:	Lock nut is included in the scope of delivery

Product properties

Product type	Panel mounting base	
Thread type	M12	
Data management status		
Article revision	05	

Connection data

Connection method	THR solder connection
Tightening torque	1.5 2 Nm

Material specifications

Material	Zinc die-cast (nickel-plated)
Material	Brass, nickel-plated (Locking nut)
Seal material	FKM
	FKM
Material for screw connection	Zinc die-cast, nickel-plated

Connector

Connection 1

Head design	Socket
Head thread type	M12

Mechanical properties

Мес	hanic	al data

Insertion/withdrawal cycles	> 100	

Environmental and real-life conditions

Ambient conditions

Degree of protection (when plugged in)	IP67 (correctly plugged in and locked)
Degree of protection	IP67 (correctly plugged in and locked)
	IP67, when in locked state
Ambient temperature (operation)	-25 °C 85 °C (Plug / socket)



1414003

https://www.phoenixcontact.com/pc/products/1414003

	-40 °C 85 °C (without mechanical actuation)
tandards and regulations	
M12	
Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101
Note	In line with
ounting	
Mounting type	Rear mounting M15 x 1 Spacing between the top edge of the PCB and the back of the front plate: 7 mm
Thread type	()
Assembly note	Spacing between the top edge of the PCB and the back of the front plate: 7 mm



1414003

https://www.phoenixcontact.com/pc/products/1414003

Classifications

UNSPSC 21.0

ECLASS

202.00		
	ECLASS-11.0	27440224
	ECLASS-12.0	27440224
	ECLASS-13.0	27440224
ETIM		
	ETIM 9.0	EC003556
UNSPSC		

31171600



1414003

https://www.phoenixcontact.com/pc/products/1414003

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	7de52a07-778d-4726-8d73-9fd6086284c1

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com