



Connectors > Automotive Connectors > Automotive Housings > MCON 1.2, 1-row, 2-8 POS TAB Housing, Sealed



Connector System: **Wire-to-Wire**
Number of Positions: **5**
Connector & Housing Type: **Housing for Male Terminals**
Centerline (Pitch): **4 mm [.157 in]**
Sealable: **Yes**

[All MCON 1.2, 1-row, 2-8 POS TAB Housing, Sealed \(20\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal

Configuration Features

Number of Positions	5
Number of Rows	1

Electrical Characteristics

Operating Voltage	14 VDC
Nominal Voltage Architecture	12 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	A



Contact Features

Contact Size	1.2mm
Contact Type	Tab
Mating Tab Width	1.2 mm[.047 in]
Contact Current Rating (Max)	24 A

Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	4 mm[.157 in]

Dimensions

Connector Height	16.3 mm[.642 in]
Product Width	44 mm[1.732 in]
Product Length	25.9 mm[1.02 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F]
Operating Temperature Range	-40 – 130 °C[-40 – 266 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Packaging Features

Packaging Quantity	750
Packaging Method	Package

Other

Serviceable	No
Connector Position Assurance Capable	No



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 967056-1
MQS BLINDSTOPFEN4MM



TE Part # 967067-1
MQS SGL WIRE SEAL



TE Part # 967067-2
MQS EINZELLEITDICHT



TE Part # 1-1718806-1
5POS, MCON 1.2 LL REC SEALED



TE Part # 1-1670921-1
5POS, MCON 1.2 LL REC SEALED



TE Part # CAT-N13-MSLRTT12
MCON 1.2 Locking Lance Receptacle and Tab Terminals



TE Part # CAT-N14-NMRH12128
NextGen MCON 1.2, 1-row, 2-8 POS Receptacle Housing, Sealed



TE Part # 3-1579028-8
EXTRACTION TOOL






TE Part # 3-1579028-6
TOOL FOR SECONDARY LOCK



TE Part # 1-2141521-1
5POS,TAB 1.2X0.6 CB,PIN HSG,SE




TE Part # 1718761-3
MCON 1.2 LL TAB SWS AG LP




TE Part # 2141522-1
RETAINER,TE,5POS.

Also in the Series


MCON 1.2mm




Automotive Connector Caps & Covers
(18)




Automotive Connector Locks &
Position Assurance(10)




Automotive Housings(328)




Automotive Terminals(96)



Connector Seals & Cavity Plugs(11)



Insertion & Extraction Tools(5)



Other Automotive Connector
Accessories(7)


Customers Also Bought




TE Part #926539-3
250 FASTON HSG. REC. 1P BLACK



TE Part #1326136-1
26WAY LAC "SINGLE GEAR" ASMBLY



TE Part #1-1326032-1
2.8MM RECP,SEAL,14AWG,REV REEL



TE Part #623346-1
2P CONNECTOR HOUSING




TE Part #1813112-1
MCP 1.5&2.8 HYB 28P PLUG ASS'Y



TE Part #5-1418758-3
MCON 1.2 LL TAB STC AG



TE Part #6-1971773-4
PTL 1X4 PLUG HSG HIGH TEMP KEY
B RED



TE Part #2098377-2
20P PLUG ASSEMBLY UNSEALED
HYBRID B-KEY



Documents

Product Drawings

5POS, MCON 1.2 LL TAB SEALED COD A

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-2141520-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2141520-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2141520-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English