



+ RELAYS, CONTACTORS & SWITCHES
PROTECTIVE RELAYS



✓ Active

TE CONNECTIVITY (TE)
WUVT3-220=WILMAR UNDERVOLTAGE
CII | WUVT

WUVT3-220
TE Internal Number: 1-1618113-4

Not EU RoHS Compliant
Not EU ELV Compliant
Contact Arrangement 1 Form A, SPST-NO, 1 NO
Contact Current Rating (A) 5
Input Voltage (VAC) 220
Time Delay With
Phase Three

↓ PRODUCT DRAWING
English

DOCUMENTATION

Product Drawings
SD-WUVT3-=UNDervoltage Relay, Series
PDF
English

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.
Please Note: Use the Product Drawing for all design activity.

Product Type Features

Protection Function Undervoltage
Time Delay With
Phase Three
Product Type Relay
Relay Type Protective Relay

Electrical Characteristics

Input Voltage (VAC) 220
Actuating System AC

Signal Characteristics

Frequency Adjustment (Hz) 50 – 400

Contact Features

Type of Control Potentiometer Adjustable
Contact Arrangement 1 Form A, SPST-NO, 1 NO
Contact Current Rating (A) 5
Contact Arrangement (Additional Output) 1 Form B, SPST-NC, 1 N/C

Dimensions

Dimensions (L x W x H) (Approximate) 107.95 x 114.3 x 96.7 mm [4.25 x 4.5 x 3.81 in]

Usage Conditions

Operating Temperature Range (°C) -40 – 70

Operation/Application

Mode of Operation Adjustable Drop-Out

PRODUCT COMPLIANCE

+

Statement of Compliance

Statement of Compliance
PDF