




E-NETTR 10/100/1000Base-T DUAL Port Transformer Module

P/N: H4801G


- * Designed to meet IEEE802.3ab requirement
- * Lead-Free & Designed to meet RoHS requirement
- * Designed to meet IR255°C peak requirement
- * Primary inductance 350uH Min with 8mA DC Bias
- * Single Port for NIC Application
- * Operating temperature range -40°C to +85°C
- * Storage temperature range:-40°C to +85°C
- * Product made in China, product weight:3.0g
- * MSL=1



Electrical Specifications@25°C

Part Number	Turn Ratio (±3%)	Insertion Loss 1~100MHz (dB Max)	Return Loss (dB Min)				Cross Talk (dB Min)			DCMR (dB Min)			Hi-Pot (Vrms MIN)
			1-30MHz	40-60MHz	60-80MHz	100MHz	30MHz	60MHz	100MHz	30MHz	60MHz	100MHz	
H4801G	1CT:1CT	-1.0	-18	-13.1	-12	-10	-35	-30	-30	-43	-37	-33	1500


Mechanical



Unless otherwise specified tolerances: xx.xo ± 0.25 mm

o.xx ± 0.05 mm

Schematics



东莞市祥星电子有限公司

地址：东莞市石碣镇横滘科技中路第三工业区

TEL:0769-86384669

FAX:0769-81813600

Miss Xie: 13549396638

xxing.guang@163.com

[Http://www.e-nettr.com](http://www.e-nettr.com)