





Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	1

LIQUID CRYSTAL DISPLAY MODULE
MODEL: NMTC-F20401DFWHSGW
Customer's No.: None.

Acceptance

Microtips Technology Inc.
 12F. No.31 Lane 169, Kang Ning St., His-Chih,
 Taipei Hsien, Taiwan, R.O.C.
 FAX: 886-2-26958625

Approved and Checked by

Approved by	Checked by		Made by
			



Microtips Technology Inc.

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	2

Revise Records

Rev.	Date	Contents	Written	Approved
A	2020/05/06	Initial Edition	Lewis	Danny

Special notes

Note1.	White Edge-Lite LED Backlight
Note2.	
Note3.	
Note4.	
Note5.	

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	3

CONTENTS

1. General Specifications.....	4
2. Electrical Specifications.....	5
3. Optical Specification.....	8
4. I/O Terminal.....	11
5. Reliability Test.....	13
6. Appearance Standards.....	15
7. Handling and Precautions.....	18
8. Warranty	19
9. Dimensional Outline.....	20

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	4

1. General Specifications

Operating Temperature.	: Min. -20°C ~ Max. 70°C
Storage Temperature.	: Min. -30°C ~ Max. 80°C
Display Format	: 20 characters x 4 lines
Display Fonts	: 5 x 7 dots + cursor (1 character)
Viewing Area	: 76.0 (W) x 25.2 (H) mm
Outline Dimensions	: 98.5 (W) x 61.0 (H) x 15.6 max. (D) mm
Weight	: None.
LCD Type	: FSTN / Black&White-mode / Transflective
Viewing Angle	: 6:00
Backlight	: LED Edge-Lite (White Color)
Drawings	: As attached drawings
Controller Drive IC	:ST7066U
Weight	:74.2g max

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	5

2. Electrical Specifications

2.1 Absolute Maximum Ratings

$V_{SS} = 0V$

Parameter	Symbol	Conditions	Min.	Max.	Units
Supply Voltage (Logic)	$V_{DD} - V_{SS}$	--	- 0.3	7.0	V
Supply Voltage (LCD Drive)	$V_{DD} - V_{EE}$	--	0	13.5	V
Input Voltage	V_I	--	- 0.3	$V_{DD} + 0.3$	V

2.2 DC Characteristics

$T_a = 25^\circ C, V_{SS} = 0V$

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Supply Voltage (Logic)	$V_{DD} - V_{SS}$	--	4.5	--	5.5	V
Supply Voltage (LCD Drive)	$V_{DD} - V_{EE}$	Shown in 3.1				V
High Level Input Voltage	V_{IH}	$V_{DD} = 5.0V \pm 10\%$	2.2	--	V_{DD}	V
Low Level Input Voltage	V_{IL}	$V_{DD} = 5.0V \pm 10\%$	-0.3	--	0.8	V
High Level Output Voltage	V_{OH}	$I_{OH} = -0.205mA$	2.4	--	V_{DD}	V
Low Level Output Voltage	V_{OL}	$I_{OL} = 1.2mA$	0	--	0.4	V
Supply Current	I_{DD}	$V_{DD} - V_{SS} = 5.0V$	--	2.8	4.2	mA

2.3 AC Characteristics

$V_{CC} = 5.0V \pm 10\%$

Parameter	Symbol	Conditions	Min.	Max.	Units
Enable Cycle Time	t_{CYC}	Fig.1, 2	500	--	ns
Enable Pulse Width	PW_{EH}	Fig.1, 2	300	--	ns
Enable Rise/Fall Time	t_{Er}, t_{Ef}	Fig.1, 2	--	25	ns
Address Setup Time	t_{AS}	Fig.1, 2	60	--	ns
Address Hold Time	t_{AH}	Fig.1, 2	10	--	ns
Write Data Setup Time	t_{DSW}	Fig.1	60	--	ns
Write Data Hold Time	t_{DHW}	Fig.1	10	--	ns
Read Data Delay Time	t_{DDR}	Fig.2	--	190	ns
Read Data Hold Time	t_{DHR}	Fig.2	20	--	ns



Microtips Technology Inc.

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHS GW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	6




Fig.1 Write Operation Timing




Fig.2 Read Operation Timing

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	7

2.4 Lighting Specifications

2.4.1 Absolute Maximum Ratings


Ta = 25°C

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Forward Current	IF	--	--	--	200	mA
Reverse Voltage	VR	--	--	--	12	V
LED Power Dissipation	PD	--	--	--	240	mW

2.4.2 Operating Characteristics

Ta = 25°C

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Forward Voltage	V _F	I _F = 160mA	--	12	--	V
Luminance of Backlight Surface	L	I _F = 160mA	--	750	--	cd/m ²
Chromaticity Coordinates	x	--	0.28	0.31	0.34	
	y	--	0.29	0.32	0.35	



Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	8

3. Optical Specifications

3.1 LCD Driving Voltage

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Recommended LCD Driving Voltage Note 1	$V_{DD} - V_{EE}$	Ta = -20 °C	5.74	5.02	4.37	V
		Ta = 25 °C	4.88	4.49	4.09	V
		Ta = 70 °C	4.59	4.25	3.90	V

Note 1: Voltage (Applied actual waveform to LCD Module) for the best contrast. The range of minimum and maximum shows tolerance of the operating voltage. The specified contrast ratio and response time are not guaranteed over the entire range.

3.2 Optical Characteristics

Ta=25 °C, 1/16 Duty, 1/5 Bias, V_{CC} = 4.5V (Note 4), $\theta = 0^\circ$, $\phi = 270^\circ$

Parameter		Symbol	Conditions	Min.	Typ.	Max.	Units
Contrast Ratio Note 1		CR	Ta = 25 °C	--	5	--	--
Viewing Angle		--	Shown in 3.3				
Response Time	Rise Note 2	T _{ON}	Ta = 25 °C	--	160	320	ms
	Decay Note 3	T _{OFF}	Ta = 25 °C	--	155	310	ms

Note 1: Contrast ratio is defined as follows.

$$CR = L_{OFF} / L_{ON}$$

L_{ON}: Luminance of the ON segments, L_{OFF}: Luminance of the OFF segments


Note 2: The time that the luminance level reaches 90% of the saturation level from 0% when ON signal is applied.

Note 3: The time that the luminance level reaches 10% of the saturation level from 100% when OFF signal is applied.

Note 4: Definition of Driving Voltage V_D. Assuming that the typical driving waveforms shown below are applied to the LCD Panel at 1/A Duty - 1/B Bias (A: Duty Number, B: Bias Number). Driving voltage V_D is defined as follows: $V_D = (V_{th1} + V_{th2}) / 2$


V_{th1}: The voltage VO-P that should provide 50% of the saturation level in the luminance at the segment which the ON signal is applied to.

V_{th2}: The voltage VO-P that should provide 50% of the saturation level in the luminance at the segment which the OFF signal is applied to.




Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	9

3.3 Definition of “Vth”




- (a).Vth1: $\phi = 270^\circ$, $\theta_1= 10^\circ$, Selected Waveform 50% Transmittance
- (b).Vth2: $\phi = 270^\circ$, $\theta_1= 40^\circ$, Non–Selected Waveform 30% Transmittance




Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	10

3.4 Definition of Viewing Angle

Viewing Direction: $\Phi = 270$ degree



3.5 Definition of Response Time



3.6 Definition of Contrast Ratio

Contrast Ration =
$$\frac{\text{Transmittance under Selected Waveform}}{\text{Transmittance under Non-Selected Waveform}}$$

Measurement Condition: Viewing Angle: $\theta_2 = 0^\circ, \theta_1 = 0^\circ$

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	11


4. I/O Terminal

4.1 Pin Assignment

No.	Symbol	Level	Function
1.	VSS	--	Power Supply (0V, GND)
2.	VCC	--	Power Supply for Logic
3.	VO	--	Power Supply for LCD Drive
4.	RS	H / L	Register Select Signal
5.	R/W	H / L	Read/Write Select Signal H : Read L : Write
6.	E	H / L	Enable Signal (No pull-up Resister)
7.	DB0	H / L	Data Bus Line
8.	DB1	H / L	Data Bus Line
9.	DB2	H / L	Data Bus Line
10.	DB3	H / L	Data Bus Line
11.	DB4	H / L	Data Bus Lin
12.	DB5	H / L	Data Bus Line
13.	DB6	H / L	Data Bus Line
14.	DB7	H / L	Data Bus Line
15.	LEDA	--	Power Supply for Backlight /LED Anode (+)
16.	LEDK	--	Power Supply for Backlight /LED Cathode (-)


4.2 Example of Power Supply

It is recommended to apply a potentiometer for the contrast adjust due to the tolerance of the driving voltage and its temperature dependence.



Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	12

4.3 Block Diagram




Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	13

5. Reliability Test

5.1 Test Item

No change on display and in operation under the following test condition.

No.	Test Item	Description	Condition	Note
1.	High Temperature (Operation)	Durability test under long time high temperature with electrical stress (voltage, current)	80°C ± 2°C 240hrs	--
2.	High Temperature (Storage)	Durability test under long time high temperature storage	70°C ± 2°C 240hrs	4
3.	Low Temperature (Operation)	Durability test under long time low temperature with electrical stress (voltage, current)	30°C ± 2°C, 240hrs	3
4.	Low Temperature (Storage)	Durability test under long time low temperature storage	-20°C ± 2°C, 240hrs	3, 4
5.	Damp Proof Test	Durability test under long time high temperature and high humidity	60°C ± 2°C, 90% RH 96hrs	3, 4
6.	Vibration Test	Total fixed amplitude: 1.5mm Vibration frequency: 10~55Hz One cycle 60 seconds to 3 directions of X, Y, Z for each 15 minutes	--	5
7.	Shock Test	<p>To be measured after dropping from 60cm high on the concrete surface in packing state.</p>  <p>Dropping method corner dropping A corner: once</p> <p>Edge dropping B, C, D edge: once</p> <p>Face dropping E, F, G face: once</p>		

Note 1: Unless otherwise specified, tests will be conducted under the following condition,

Temperature : 25°C ± 2°C

Humidity : 65% ± 5%

Note 2: Unless otherwise specified, tests will be not conducted under functioning state.

Note 3: No dew condensation to be observed.

Note 4: The function test shall be conducted after 4 hours storage at the normal temperature and humidity after removed from the test chamber.

Note 5: Vibration test will be conducted to the product itself without putting it in a container.

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	14

5.2 Judgment Standard

Failure Mode	Test Item							Judgment Standard
	1	2	3	4	5	6	7	
Orientation	*	*	*	*	*			No remarkable degradation of appearance under bias/ non-bias condition
Current Value (IAC)	*	*	*	*	*			No remarkable increase
Contrast	*		*	*	*			No remarkable poor contrast
Domain	*	*	*	*	*			Less than 20% of all dots have reverse tilt of more than on third of one dot area.
Bubble (Inside Cell)	*	*	*	*	*	*		As per “Appearance Standard” (Note. including one which disappear after 25°C 2H)
Polarizer	*				*	*		As per “Appearance Standard” no remarkable appearance change
Glass Damage							*	As per “Appearance Standard”

Note. 1. * is strong linkage between Failure Mode and Test Item.

2. Number of Test Item should be referred to former page.


3. Judgment and Standard value should be fixed by other inspection standard and criteria samples.

Messrs.	Standard				
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	15


6. **Appearance Standards**

6.1 Inspection Conditions

The LCD shall be inspected under 40W white fluorescent light.
The distance between the eyes and the sample shall be more than 30cm.
All directions for inspecting the sample should be within 45° against perpendicular line.



6.2 Definition of Applicable Zones







A. Zone: Active display area
B. Zone: Area from outside of "A Zone" to validity viewing area
C. Zone: Rest parts
A Zone + B Zone = Validity viewing area

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	16

6.3 Standards

No.	Parameter	Criteria																												
1.	Black and White Spots, Foreign Substances	(1) Round Shape																												
		<table><tr><th><div>Zone</div><div>Dimension (mm)</div></th><th colspan="3">Acceptable Number</th></tr><tr><th></th><th>A</th><th>B</th><th>C</th></tr><tr><td>D ≤ 0.1</td><td>*</td><td>*</td><td>*</td></tr><tr><td>0.1 < D ≤ 0.2</td><td>3</td><td>5</td><td>*</td></tr><tr><td>0.2 < D ≤ 0.25</td><td>2</td><td>3</td><td>*</td></tr><tr><td>0.25 < D ≤ 0.3</td><td>0</td><td>1</td><td>*</td></tr><tr><td>0.3 < D</td><td>0</td><td>0</td><td>*</td></tr></table>	<div>Zone</div> <div>Dimension (mm)</div>	Acceptable Number				A	B	C	D ≤ 0.1	*	*	*	0.1 < D ≤ 0.2	3	5	*	0.2 < D ≤ 0.25	2	3	*	0.25 < D ≤ 0.3	0	1	*	0.3 < D	0	0	*
		<div>Zone</div> <div>Dimension (mm)</div>	Acceptable Number																											
			A	B	C																									
		D ≤ 0.1	*	*	*																									
		0.1 < D ≤ 0.2	3	5	*																									
		0.2 < D ≤ 0.25	2	3	*																									
		0.25 < D ≤ 0.3	0	1	*																									
		0.3 < D	0	0	*																									
		D = (Long + Short)/2 *: Disregard																												
		(2) Line Shape																												
		<table><tr><th><div>Zone</div><div>X (mm) Y (mm)</div></th><th colspan="3">Acceptable Number</th></tr><tr><th></th><th>A</th><th>B</th><th>C</th></tr><tr><td>-- 0.03 ≥ W</td><td>*</td><td>*</td><td>*</td></tr><tr><td>2.0 ≥ L 0.05 ≥ W</td><td>3</td><td>3</td><td>*</td></tr><tr><td>1.0 ≥ L 0.1 ≥ W</td><td>3</td><td>3</td><td>*</td></tr><tr><td>-- 0.1 < W</td><td colspan="3">In the same way (1)</td></tr></table>	<div>Zone</div> <div>X (mm) Y (mm)</div>	Acceptable Number				A	B	C	-- 0.03 ≥ W	*	*	*	2.0 ≥ L 0.05 ≥ W	3	3	*	1.0 ≥ L 0.1 ≥ W	3	3	*	-- 0.1 < W	In the same way (1)						
		<div>Zone</div> <div>X (mm) Y (mm)</div>	Acceptable Number																											
	A	B	C																											
-- 0.03 ≥ W	*	*	*																											
2.0 ≥ L 0.05 ≥ W	3	3	*																											
1.0 ≥ L 0.1 ≥ W	3	3	*																											
-- 0.1 < W	In the same way (1)																													
X : Length Y: Width *: Disregard																														
Total defects shall not exceed 5.																														
2.	Air Bubbles (between glass & polarizer)	<table><tr><th><div>Zone</div><div>Dimension (mm)</div></th><th colspan="3">Acceptable Number</th></tr><tr><th>A</th><th>B</th><th>C</th></tr><tr><td>D ≤ 0.3</td><td>*</td><td>*</td><td>*</td></tr><tr><td>0.3 < D ≤ 0.4</td><td>3</td><td>*</td><td>*</td></tr><tr><td>0.4 < D ≤ 0.6</td><td>2</td><td>3</td><td>*</td></tr><tr><td>0.6 < D</td><td>0</td><td>0</td><td>*</td></tr></table>	<div>Zone</div> <div>Dimension (mm)</div>	Acceptable Number			A	B	C	D ≤ 0.3	*	*	*	0.3 < D ≤ 0.4	3	*	*	0.4 < D ≤ 0.6	2	3	*	0.6 < D	0	0	*					
		<div>Zone</div> <div>Dimension (mm)</div>	Acceptable Number																											
		A	B	C																										
		D ≤ 0.3	*	*	*																									
		0.3 < D ≤ 0.4	3	*	*																									
		0.4 < D ≤ 0.6	2	3	*																									
		0.6 < D	0	0	*																									
		*: Disregard																												
		Total defects shall not exceed 3.																												

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	17

No.	Parameter	Criteria
3.	The Shape of Dot	<p>(1) Dot Shape (with Dent)</p>  <p>As per the sketch of left hand.</p>
		<p>(2) Dot Shape (with Projection)</p>  <p>Should not be connected to next dot.</p>
		<p>(3) Pin Hole</p>  <p>$(X+Y)/2 \leq 0.2\text{mm}$ (Less than 0.1mm is no counted.)</p>
		<p>(4) Deformation</p>  <p>$(X+Y)/2 \leq 0.2\text{mm}$</p>
		<p>Total acceptable number: 1/dot, 5/cell (Defect number of (4): 1pc.)</p>
4.	Polarizer Scratches	Not to be conspicuous defects.
5.	Polarizer Dirts	If the stains are removed easily from LCDP surface, the module is not defective.
6.	Complex Foreign Substance Defects	Black spots, line shaped foreign substance or air bubbles between glass & polarizer should be 5pcs maximum in total.
7.	Distance between different Foreign Substance defects	$D \leq 0.2$: 20mm or more $0.2 < D$: 40mm or more

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	18

7. **Handling and Precautions**

The Following precautions will guide you in handling our product correctly.

- 1 Liquid crystal display devices
 - 1.1 The liquid crystal display device panel used in the liquid crystal display module is made of plate glass. Avoid any strong mechanical shock. Should the glass break handle it with care.
 - 1.2 The polarizer adhering to the surface of the LCD is made of a soft material. Guard against scratching it.
- 2 Care of the liquid crystal display module against static electricity discharge.
 - 2.1 When working with the module, be sure to ground your body and any electrical equipment you may be using. We strongly recommend the use of anti static mats (made of rubber), to protect work tables against the hazards of electrical shock.
 - 2.2 Avoid the use of work clothing made of synthetic fibers. We recommend cotton clothing or other conductivity-treated fibers.
 - 2.3 Slowly and carefully remove the protective film from the LCD module, since this operation can generate static electricity.
- 3 When the LCD module alone must be stored for long periods of time:
 - 3.1 Protect the modules from high temperature and humidity.
 - 3.2 Keep the modules out of direct sunlight or direct exposure to ultra-violet rays.
 - 3.3 Protect the modules from excessive external forces.
- 4 Use the module with a power supply that is equipped with an over current protector circuit, since the module is not provided with this protective feature.
- 5 Do not ingest the LCD fluid itself should it leak out of a damaged LCD module. Should hands or clothing come in contact with LCD fluid, wash immediately with soap.
- 6 Conductivity is not guaranteed for models that use metal holders where solder connections between the metal holder and the PCB are not used. Please contact us to discuss appropriate ways to assure conductivity.

Messrs. Standard					
Product Specification	Model:	NMTC-F20401DFWHSGW	Rev. No.	Issued Date.	Page.
			A	MAY. 06, 20	19

8. Warranty

This product has been manufactured to your company's specifications as a part for use in your company's general electronic products. It is guaranteed to perform according to delivery specifications. For any other use apart from general electronic equipment, we cannot take responsibility if the product is used in medical devices, nuclear power control equipment, aerospace equipment, fire and security systems, or any other applications in which there is a direct risk to human life and where extremely high levels of reliability are required. If the product is to be used in any of the above applications, we will need to enter into a separate product liability agreement.


- 1 13-month guarantee starts from the date code.
- 2 We cannot accept responsibility for any defect, which may arise from additional manufacturing of the product (including disassembly and reassembly), after product delivery.
- 3 We cannot accept responsibility for any defect, which may arise after the application of strong external force to the product.
- 4 We cannot accept responsibility for any defect, which may arise due to the application of static electricity after the product has passed your company's acceptance inspection procedures.
- 5 We cannot accept responsibility for industrial property, which may arise through the use of your product, with exception to those issues relating directly to the structure or method of manufacturing of our product. Microtips-origin longer than 2 (two) years from Microtips production or 1(one) year from Microtips overseas agent or distributor delivery which ever comes later.


9. Dimensional Outlines

- See the next page.....



Microtips Technology Inc.








REV.	DESCRIPTION	DRAWN	CHECK	APP'D	DATE
△	Production Release	Atom	Jummou	Danny	20191219
△	Revise Backlight Dimension	Atom	Jummou	Danny	20200616

PIN Assignment (CN1)	
NO.	SYMBOL
1	VSS
2	VCC
3	VEE
4	RS
5	R/W
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	LED: ANODE
16	LED: CATHODE

Pin Assignment (CN2)	
1	LED: CATHODE
2	LED: ANODE

Notes:

- 1.DISPLAY TYPE:FSTN/Black&White mode
- 2.VIEW DIRECTION: 6 O'CLOCK
- 3.POLARIZER TYPE:TRANSFLECTIVE/POSITIVE
- 4.DRIVER METHOD:1/16 DUTY 1/4 BIAS
- 5.LCD DRIVING VOLTAGE:4.8V
- 6.LOGIC SUPPLY VOLTAGE:5V
- 7.OPERATING TEMP:-20~+70
- 8.STORAGE TEMP:-30~+80
- 9.CONTROLLER/DRIVE IC:ST7066U
- 10.BACKLIGHT:White,Vf=12V,If=160mA,750 cd/m2



913-20401DAA		1	20191219		
NO.	PART NAME	Q'TY	DATE:	MATERIAL	FINISH
		DRAWN	CHECK	APP'D	UNIT:MM
		Atom	Jummou	Danny	SCALE: 1 / 1
				P/N: NMTC-F20401DFWHSW	
				DWG NO.: C20401D0	
				FILE:	
				SHEET 1/ 1	
				Rev: B	