



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Housing**

Connector & Housing Type: **Plug**

Connector System: **Wire-to-Panel, Wire-to-Wire**

Number of Positions: **3**

Centerline (Pitch): **4.2 mm [.165 in]**

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Panel, Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Insertion Force	15 Newton
Compatible With Wire & Cable Type	Discrete Wire
Number of Positions	3
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Contact Layout	Inline
----------------	--------



Contact Retention Within Housing	Without
Contact Type	Pin
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	4.2 mm[.165 in]
Housing Color	White
Housing Material	Nylon 66
Dimensions	
Connector Height	7.4 mm[.291 in]
Product Width	23.9 mm[.94 in]
Product Length	13.8 mm[.543 in]
Compatible Insulation Diameter Range	1.2 – 3.1 mm[.047 – .122 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Identification Marking	
Circuit Identification Feature	With
Industry Standards	
CSA Rating	208567
UL Rating	Recognized
Compatible With Agency/Standards Products	CSA, UL
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Features	
Packaging Quantity	1000
Packaging Method	Bag



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1586106-3
3P RCPT VAL-U-LOK SR V0



TE Part # 2029056-3
3P VAL-U-LOK SR HDR SN V0 W/DH



TE Part # 2029151-3
3P R/A HDR VAL-U-LOK V0 W/P



TE Part # 2307184-3
3P PLUG SR VAL-U-LOK PM GW - TPA
VERSION



TE Part # 2029167-3
3P VAL-U-LOK SR HDR SN V0 WODH

TE Part # 2307185-3
3P PLUG SR VAL-U-LOK FH GW - TPA
VERSION

Customers Also Bought

TE Part #1586105-3
3P RCPT VAL-U-LOK SR V2

TE Part #1586106-3
3P RCPT VAL-U-LOK SR V0

TE Part #1-34070-1
PG BUTT SPLC 22-16COMM22-18MIL

TE Part #1586019-2
2P RCPT VAL-U-LOK V0

TE Part #1-480700-0
03P UMNL PLUG HSG NATL

TE Part #794956-1
VAL-U-LOK SKT BR SN 22-18AWG

TE Part #350537-1
UMNL SOK 20-14 .0126 PTPBR

TE Part #1586018-2
2P PM PLUG VAL-U-LOK V0

TE Part #1586018-4
4P PM PLUG VAL-U-LOK V0

TE Part #2-34853-1
TERM,PG, R, 12-10, #8, T&R

Documents

Product Drawings

3P PLUG VAL-U-LOK SR PM V0

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1586102-3_B_c-1586102-3-b.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_1586102-3_B_c-1586102-3-b.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1586102-3_B_c-1586102-3-b.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

English

Product Specifications

[Application Specification](#)

English

Agency Approvals

[UL Report](#)

English