

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

# 5-Outlet Surge Protector with 2 USB Ports (3.4A Shared) - 6 ft. Cord, 450 Joules, Metal Housing

# MODEL NUMBER: TLM526USBB









5-outlet surge protector safeguards your home/office electronics against dangerous surges, spikes and line noise.

#### **Features**

#### 5-Outlet Surge Protector with USB Safeguards Your Sensitive Electronics

Ideal for your home, office, retail or industrial workstation, this Protect It!® 5-outlet surge protector features a surge protection rating of 450 joules to defend your sensitive electronic components against power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLM526USBB protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

# NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your computer, printer, wireless router, desk lamp and other home/office electronics into five NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise.

#### 2 USB Ports Share 3.4 Amps of Charging Power

This surge protector with 2 USB ports is ideal for keeping your devices at full capacity. Two USB-A ports are available for charging your smartphone, tablet and other USB mobile devices, which are also protected from the damaging effects of surges, spikes and line interference.

# Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

# **Includes the Latest Safety Features**

The lighted on/off switch provides one-touch control over connected equipment. Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required.

# **Versatile Surge Protector Provides Multiple Installation Options**

This surge protector with 6-foot cord and NEMA 5-15P plug gives you flexibility in placing the unit away from the nearest wall outlet. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black metal housing.

# **Highlights**

- 5 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 450 joules protect your valuable electronics against dangerous surges and spikes
- 2 USB ports share 3.4A for fast charging of phones, tablets and other mobile devices
- 6 ft. cord with NEMA 5-15P plug allows flexibility in placing devices away from AC outlet
- Durable metal housing designed to stand up in harsh environments, such as warehouses

#### **Applications**

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

# **Package Includes**

 TLM526USBB Protect It! 5-Outlet Surge Protector, Black Metal Housing



• Owner's manual

# **Specifications**

| OVERVIEW                           |   |
|------------------------------------|---|
| UPC Code                           | 037332223470  |
| OUTPUT                             |   |
| Charging Ports / Amps              | (2) 3.4A  |
| Frequency Compatibility            | 50 / 60 Hz  |
| Output Receptacles                 | (5) 5-15R   |
| Output (Watts)                     | 1800  |
| Circuit Breaker (amps)             | 15  |
| Overload Protection                | 15A resettable illuminated combo switch / circuit breaker                         |
| Transformer Accommodation          | (3) Yes   |
| Outlet Orientation                 | Single row of 5 outlets   |
| Right-Angle Outlets                | Yes   |
| INPUT                              |   |
| Nominal Input Voltage(s) Supported | 120V AC   |
| Recommended Electrical Service     | 120V (110-125V)   |
| Input Cord Length (ft.)            | 6   |
| Input Cord Length (m)              | 1.83  |
| Input Cord Gauge Type              | 14 gauge, SJT   |
| Voltage Compatibility (VAC)        | 120   |
| Maximum Surge Amps                 | 35500   |
| Input Plug Type                    | NEMA 5-15P  |
| Right-Angle Plug                   | No  |
| Integrated Cord Clip               | No  |
| USER INTERFACE, ALERTS & CONTROLS  |   |
| Diagnostic LED(s)                  | Yes   |
| Switches                           | Combination AC circuit breaker and 2 position red illuminated on/off power switch |
| SURGE / NOISE SUPPRESSION          |   |





| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$10,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |  |
|--|---|--|
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty   |  |
| WARRANTY   |   |  |
| Approvals  | Exceeds IEEE 587 category A&B specifications  |  |
| cUL / CSA (Canada)   | cUL   |  |
| UL1363 (Power Tap)   | UL1363  |  |
| UL1449 3rd Edition (AC<br>Suppression)                     | UL1449 3rd EDITION  |  |
| CERTIFICATIONS   |   |  |
| Anti-Microbial Protected                                   | No  |  |
| Color  | Black   |  |
| Color (AC Line Cord)                                       | Black   |  |
| Receptacle Color   | Black   |  |
| Housing Color  | Black   |  |
| Integrated Keyhole Mounting Slots                          | Yes   |  |
| Material of Construction                                   | metal   |  |
| Unit Dimensions (hwd / cm)                                 | 28.91 x 4.75 x 4.44   |  |
| Unit Dimensions (hwd / in.)                                | 11.4 x 1.87 x 1.75  |  |
| Shipping Weight (kg)                                       | 0.68  |  |
| Shipping Dimensions (hwd / in.)                            | 12.99 x 4.72 x 1.97   |  |
| PHYSICAL   |   |  |
| Network (Ethernet) Protection                              | No  |  |
| Cable (Coax) Protection                                    | No  |  |
| Telephone/DSL Protection                                   | No  |  |
| DATALINE SURGE SUPPRESSION                                 |   |  |
| Auto Shut-Off  | Yes   |  |
| EMI / RFI Filtering  | Yes   |  |
| UL1449 Let Through Rating                                  | 800,800,800   |  |
| Protection Modes   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                                    |  |
| AC Suppression Response Time                               | < 1 ns  |  |
| AC Suppression Joule Rating                                | 450   |  |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>