

## Specification Sheet

Part Number: 151-03649



No drilling or extra hardware required – just secure to steel surface.

Magnetic mounts are reliable even in debris, dirt, and oil.

Use for permanent mounting or as a temporary installation tool.

Reuse and reposition capabilities allow for a flexible mounting solution.

Easily remove without residue.

|                |            |
|----------------|------------|
| Article Number | 151-03649  |
| Type           | MAGCTM20P  |
| Color          | Black (BK) |
| Quantity Per   | bag        |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description   | <p>Magnetic cable tie mounts route bundles by securing to steel surfaces without the need for a mounting hole. Simply attach the wire bundle to the mount with a cable tie and position it onto the beam, metal joist, ceiling channel, conveyor frame, or other steel surface. The pipe mount has a unique shape to adhere perfectly to steel pipes. The mounts are simple to secure and can attach to surfaces contaminated with oil or debris. Ultra-strong neodymium magnets are ideal as a permanent mount or for temporary applications. Reuse and reposition them for ultimate flexibility without needing to replace or repurchase parts. Magnetic cable tie mounts can be paired with standard T18-T50 cable ties.</p> |
| Short Description     | Magnetic Pipe Mount, 1.02", Neodymium Magnet/POM/ST, 15lb Pull Force, 10/bag                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Global Part Name      | MAGCTM20P-NDFEB45M/POM/ST-BK                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Length L (Imperial)   | 1.02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Length L (Metric)     | 26.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Fixation Method       | Magnet                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Width W (Imperial)    | 0.27                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Width W (Metric)      | 7.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Height H (Imperial)   | 0.41                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Height H (Metric)     | 10.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Diameter D (Imperial) | 0.55                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Diameter D (Metric)   | 14.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

|                                |                                                            |
|--------------------------------|------------------------------------------------------------|
| Cable Tie Width Max (Imperial) | 0.23                                                       |
| Cable Tie Width Max (Metric)   | 5.84                                                       |
| Material                       | Steel (ST) Polyacetal (POM) Neodymium alloy 45M (NDFEB45M) |
| Material Shortcut              | POM ST NDFEB45M                                            |
| Halogen Free                   | Yes                                                        |
| UV Resistant (Yes/No)          | No                                                         |
| Operating Temperature          | -40°F to +176°F (-40°C to +80°C)                           |
| Reach Compliant (Article 33)   | Yes                                                        |
| ROHS Compliant                 | Yes                                                        |
| Package Quantity (Imperial)    | 10                                                         |
| Package Quantity (Metric)      | 10                                                         |
| Customs Number                 | 8505110070                                                 |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach

to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)